

Stepping into the
next 100 years

Bona
1919 – 2019



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Product Catalogue 2019



Bona®



ЦИКЛЕВОЧНАЯ
КОМПАНИЯ
WWW.1PARKET.RU +7 (495) 545-25-85

100 Years of Passion, Performance, Pioneering

As we celebrate 100 years of passion and innovation for wood floors, we have filled this year's catalogue with even more sustainable solutions and products, all developed to bring out the beauty in floors. We have lots of exciting news, from Bona Mega ONE, the latest addition to our bestselling Bona Mega range, to Bona Inspiration, a unique design concept that brings creativity to floors.

This year we also open a new chapter by expanding our offering to include resilient floors, giving you the possibility to treat and even renovate a wide range of surfaces. Based on a century of knowledge and innovation, whether you wish to renovate a rubber floor, or add design effects to linoleum, as a professional contractor you can be assured that our complete range of solutions deliver performance, value and excellent results.



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Swedish heritage

Bona AB is a family-owned company founded in 1919. With its headquarters in Sweden, Bona is now present in more than 70 different countries all over the world through subsidiaries and distributors. Recommended by professionals, Bona is the foremost leader in care and maintenance treatments for the hardwood floor industry, with a wealth of innovation and knowledge all focused on bringing out the beauty in floors.

Quality and performance

Bona provides products for the installation, renovation and maintenance of floors, to extend their lifetime. We also supply UV coatings to leading international wood floor producers. Our innovative products and systems inspire floor owners to renovate instead of replacing old or damaged floors.

Bona stands for premium quality and excellent performance. Our products are developed with a long-term sustainable perspective in mind. As a pioneer in waterborne finishes, we take into account not just the floor, but the working conditions of the craftsman and environmental impact.

**BRINGING OUT
THE BEAUTY IN FLOORS
SINCE 1919**

Bona®

All our products and solutions are supported by a century of knowledge, which we share through guidance and training, enabling our partners and customers alike to rely on our wealth of expertise, whatever the challenge.

The next century

Our 100-year heritage of creating pioneering solutions and treatments for wood floors has given us the knowledge and experience to expand our offering to the widest possible range of floors and surfaces. From stone and tile, to laminate and resilient, we are confident that our expertise can be applied to develop the same premium products for the best possible results, not just for wood floors, but for all floors.






ЦИКЛЕВОЧНАЯ
КОМПАНИЯ
WWW.1PARKET.RU +7 (495) 545-25-85

New looks for beloved floors



Garden Atmosphere




New Modern



Nordic Shimmer



Touch of Grace



Malibu Dreams



Contents

Fastening

Screed Repair	3
Moisture Barriers	4
Primers	5
Levelling Compounds	7
Underlayments	9
Water-based Adhesives	10
PU Adhesives – Reactive	11
Silane Adhesives – Reactive	12
Fillers and Repairs	14
Application Tools	15
Other Products	15

Sanding

Dust Free Sanding	17
Belt Sanders	19
Expansion Sanders	21
Edgers	22
FlexiSand System	24
Buffing Machines	28
Vacuum Cleaners	30
Other Machines	31
Superior – Ceramic Mix	32
Premium – Zircon Mix	33
Standard – Aluminium Oxide	36
Standard – Silicon Carbide	37
Pads	39
Scrad Pads	40
Screens	41
Diamond Abrasives	42
Abrasives Delta	42
Abrasives	43

Coatings

Primers	45
Lacquers	47
Sportive System	52
Oils – Wear Treatment	55
Oils – Effect Treatment	57
Oils – Outdoor	58
Fillers and Repairs	58
Resilient System	60
Resilient Maintenance	61

Floor Care

Deep Clean System	63
Lacquer – Maintenance	64
Oils – Maintenance	66

Tools & Accesories

Coatings	69
Fastening	75
Measurement	77
Occupational Safety	78
Floor Care	79

Application Advice

Lacquer System	81
Natural Wood Look	82
Sportive System	83
Craft Oil 2K System	84
Oil System	85
Hardwax Oil	87
Adhesive Guidelines	88
Index of Bona Adhesives	89

Index

Index – Products	90
Index – Article Numbers	92



Fastening

Success begins with a good foundation. And good fastening, with the right combination of strength and elasticity, is the first step to achieving a beautiful and lasting wooden floor. At Bona, our continuous R&D and dialogues with craftsmen have equipped us with what it takes to offer perfection in our craft. In this section, you will find all the products and accessories you need to lay the best foundation, regardless of subfloor type, dampness and evenness.

- | | |
|--------------------------|--------------------------------|
| 1. Screed Repair | 7. PU Adhesives - Reactive |
| 2. Moisture Barrier | 8. Silane Adhesives - Reactive |
| 3. Primers | 9. Fillers & Repair |
| 4. Levelling Compounds | 10. Application Tools |
| 5. Underlayments | 11. Other Products |
| 6. Water-based Adhesives | |



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Screed Repair

Article number

Packaging

Pcs/transport
package

Package/
pallet

Bona R405



High viscosity, two-component polyester resin for screed repair prior to application of adhesives or levelling compounds.

Key Benefits:

- Quick drying
- High viscosity
- Excellent adhesion to many substrates

Technical Data:

Base: 2-comp polyester resin + hardener
Drying time: 30–60 min
Application: Stainless steel trowel

BR40501400DEBO

1.25 kg

6

384

Bona R440



Bona R440 is a solvent-free (accord. to TRGS 610), two-component silicate based cast resin with very low emission (EC1-R Plus). It is suitable for the fast and nonpositive repair and filling of cracks and joints in screeds. Furthermore, it can be used to bond metal profiles and nail bars. Both components can be mixed quickly and easily by shaking. Bona R440 is ready to use within a few seconds.

Key Benefits:

- Very low emission EC1-R Plus
- No tools required for mixing
- Odour-free
- Fast drying

Technical Data:

Base: Sodium Silicate (water glass) and Isocyanides (Hardener)
Colour: Yellow/beige
Viscosity: Fluid
Density: 1.3 g/cm³ (immediately after mixing)

BR44006600DEBO

2 x 300 ml

5 Sets

Wave bonders



Metal strips (70 x 6 mm) for crack repairs in screeds. Use in combination with Bona R405.

AX34040000

100 pieces

100

Bona RenoForce



Bona RenoForce is a fibre glass weave to be used for the reinforcement of existing cracks and construction joints up to 5 mm in width, for screeds, concrete substrates, or between different type of subfloors. The installation of Bona RenoForce is easy and fast. It should be used in combination with either one of our Bona polyurethane adhesives such as Bona R777, Bona Titan or with the levelling compound Bona H610.

Key Benefits:

- No hazardous product
- Safe in use, promise a lasting result
- The usage of liquid resins is no longer necessary

Technical Data:

Product type: Sodium-silicate glass fibres
Colour: White
Tensile strength on filament (fibre): 3,500 N/mm²

BH500033

0.8 x 45 m

1

Fastening

Sanding

Coatings

Floor Care

Accessories



ЦИКЛЕВОЧНАЯ
КОМПАНИЯ
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Fastening

Moisture Barriers

Bona R410



A two-component epoxy resin for damp-proofing concrete or cementitious subfloors with up to 5 CM% (or 90% RH) in humidity. Can also be used as a primer for PU and silane adhesives, levelling compounds and as a light reinforcement of weak subfloors.

Key Benefits:

- Excellent damp proofing
- Excellent adhesion to most substrates
- Subfloor strengthening properties

Technical Data:

Base: 2-comp epoxy resin
Pot life: Approx. 20 min
Consumption: Approx. 150–500 g/m²
Application: Brush, roller, mohair roller

BR41002000GBBO

5 kg

1

60

Bona R540



Key Benefits:

- Moisture inhibiting
- Excellent penetration properties
- 1-component and ready to use

Technical Data:

Base: 1-comp PU
Drying time: 1–24 h, depending on type of adhesive
Application: Stainless steel trowel, mohair roller, brush

BR54002200M1BO

8 kg

1

60

Bona R590



Key Benefits:

- Reinforcing effect
- Suitable for all Bona silane or polyurethane adhesives
- Fast drying
- Product contains no liquid extenders or components that can migrate after curing

Technical Data:

Base: 1-comp silane modified
Drying time: 4–6 h
Tools of application: Bona 500F notched trowel or flat trowel
Consumption: 150–500 g/m²

BR59005000M1BO

8 kg

1

60



Fastening

Primers

Article number

Packaging

Pcs/transport package

Package/pallet

Bona D500



Primer for the preparation of absorbent and non-absorbent substrates prior to the use of dispersion-based parquet adhesives. Binds dust and reduces water absorption of substrate. Note: Not to be used with silane-based adhesives.

Key Benefits:

- Vapour permeable
- Solvent-free
- Good elasticity

Technical Data:

Base: 1-comp acrylate
Drying time: 1–24 h (depending on the subfloor)
Application: Brush, roller
Consumption: 1 part D500 to 1 part water
 Consumption: Approx. 150 g/m² (mixture)

BD50102000GBBO

5 L

3

132

Bona D501



Primer for the preparation of absorbent and non-absorbent substrates prior to the use of silane or polyurethane-based adhesives. Binds dust effectively. Use undiluted.

Key Benefits:

- Vapour permeable
- Solvent-free
- Very quick drying

Technical Data:

Base: 1-comp acrylate
Drying time: 1–2 h
Application: Brush, roller
Consumption: Approx. 150 g/m²

BD50102000GBBO

5 L

3

132

Bona D510



Primer for the preparation of absorbent substrates prior to using levelling compounds. Bona D510 reduces the absorbency of the subfloor and improves flow and adhesion of the levelling compound.

Key Benefits:

- Vapour permeable
- Solvent-free
- Excellent adhesion to many substrates

Technical Data:

Base: 1-comp acrylate
Drying time: 1–24 h (depending on the subfloor)
Application: Brush, roller
Consumption: Approx. 150 g/m²

BD51002000DEBO

5 L

3

132

Bona S100



Bona S100 is a diluent and cleaning agent for various parquet adhesives and primers.

BS10002000DEBO

5 L

4

40

Fastening

Sanding

Coatings

Floor Care

Accessories



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Bona Power Drive NEB

Used with the Bona FlexiSand 1.9, it adds a new dimension to sanding and wire brushing wood floors.



Bona PowerRemove R

Aggressive cleaning agent which strips polish quickly and efficiently.



Bona Pure Colour

Water-based 2-component paint used for creating colour designs on resilient floors.



Bona Sportive Finish

FIBA certified for olympic competition.



Bona Mega ONE

Optimized for flooring professionals offering speed, simplicity and build.



Bona Titan

A powerful and hard adhesive with revolutionary Titanium Technology.



Bona FlexiSand 1.9

Sanding system with more power for tougher surfaces.

Product Highlights 2019

Bona System – Sustainable Innovations



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Levelling Compounds

Article number

Packaging

Pcs/transport
package

Package/
pallet

Bona H600

A cementitious, self-smoothing levelling compound specially designed for the tough strains wooden floors placed on the subfloor. Also suitable for installation of LVT's (Luxury Vinyl Tiles). Apply to 1.5–10 mm thickness.



Key Benefits:

- Self-smoothing
- Rapid hardening
- High strength

Technical Data:

Base: Cement, synthetic resin
Consumption: 1.5 kg/m²/mm
Pot life: Approx. 30 min
Treadable: After approx. 3 h
Mixing ratio: 25 kg powder : 5.75 L water
Application: Notched Blade R1 or R2, flat edge hand trowel
Drying time: 24 h up to 10 mm

BH600031DE

25 kg

1

40

Bona H605

Calcium sulphate levelling compound with practically no shrinkage and tension for exceptionally smooth surfaces. Suitable for elastic and textile floor coverings as well as parquet glued down with silane adhesives.



Key Benefits:

- Very rapid hardening
- High strength
- Practically no tension or shrinkage

Technical Data:

Base: Calcium sulphate
Pot life: 45 min
Treadable: After approx. 90 min
Mixing ratio: 25 kg powder : 5.75 L water
Application: Notched Blade R1 or R2, flat edge hand trowel
Drying time: 24 h up to 3 mm

BH605031M1

25 kg

1

40 piece

Bona H610

Bona H610 is a rapid setting and drying, slump-free mortar for internal repairs. Ideal for filling holes and cracks in screeds, repairing and refacing internal concrete stair treads and risers, cement and sand screeds, concrete floors or making good around pipe work, door and window frames.



Key Benefits:

- Rapid hardening and drying – can be covered after 60 minutes.
- Slump-free – ideal for vertical and horizontal repairs
- High strength and hardness
- Stress-relieved – low shrinkage
- CE certified

Technical Data:

Base: Special cements, synthetic resin
Consumption: 1.6 kg/m²/mm
Pot life: Approx. 15 min
Treadable: After approx. 1 h
Mixing ratio: 25 kg powder : 5.5 L water
Application: Flat edge hand trowel
Drying time: 1 h

BH610031

25 kg

1

40 pieces

Bona H660 Object

Bona H660 is a cementitious smoothing levelling compound specially designed for use under mosaic, multi-layered or solid wood parquet in commercial sectors.



Key Benefits:

- Ideal for large surfaces and objects
- Very good levelling behavior
- Ready for laying after 24 h (up to 3 mm)
- CE certified

Technical Data:

Base: Cement, polymer modified
Consumption: 1.7 kg/m²/mm
Pot life: Approx. 15–20 min
Treadable: After approx. 2–4 h
Mixing ratio: 25 kg powder : 5.0 L water
Application: Notched Blade R1 or R2, flat edge hand trowel
Drying time: 24 h up to 3 mm

BH660031DE

25 kg

1

42 pieces



Fastening

Levelling Compounds

Bona H670 Gypsum



Bona H670 is a calcium sulphate-based smoothing and levelling compound specially designed for use under mosaic, multi-layered and solid wood parquet.

Key Benefits:

- Very suitable for calcium sulphate screeds and mastic asphalt
- Good levelling behavior
- CE certified

Technical Data:

Base: Calcium sulphate, polymer modified
Consumption: 1.6 kg/m²/mm
Pot life: Approx. 25–30 min
Treadable: After approx. 2–4 h
Mixing ratio: 25 kg powder : 6.0 L water
Application: Notched Blade R1 or R2, flat edge hand trowel
Drying time: 24 h up to 5 mm

BH670031DE

25 kg

1

42 pieces

Bona Fibres



Bona Fibres are alkali-resistant reinforcement glass fibres designed primarily to increase the flexural and structural strength of Bona self-levelling compounds, e.g. Bona H600. In addition, an increase in the adhesion and strength of the levelling compound is also seen. Bona Fibres do not change the handling properties of the Bona levelling compound. The use of Bona Fibres is recommended on flexible subfloors, for example nailed/screwed down planks or board floors, such as chipboard, OSB or plywood, fixed over joints or battens.

Key Benefits:

- Easy to add and mix
- Levelling behaviour is unaffected.
- Bona Fibres will remain evenly distributed and will not 'float' to the surface.
- Increases the flexural and structural strength of the Bona levelling compounds

Technical Data:

Base: Alkali-resistant fibreglass
Colour: White
Tensile strength: 1700 N/mm²

BH500031

0.25 kg

50

27 boxes

Bona Expansion Strips



Bona Expansion Strips 50 are self-adhesive foam strips, used in order to avoid sound bridges between levelling compounds and building parts.

Key Benefits:

- Ideal for use with levelling compound and thin screeds
- Self-adhesive, easy and quick to install
- Very good grip
- Remains straight on the wall

Technical Data:

Product type: PE-Foam with fleece backing and fleece socket (self-bonding)
Dimensions: 20 m x 50 mm, rolls
Material thickness: 5 mm

BH500032

20 m

5

90

Underlayments

Bona U300



Bona U300 is an underlayment made of recycled fine PUR foam granules and cork, bound with PUR elastomers. Bona U300 can be used under parquet, laminate floors and other floor coverings. It will reduce the transmission of sound from footfall. It is also suitable for a light stress decoupling.

Key Benefits:

- DIBt approval
- Easy to install
- Suitable for use with various Bona adhesives

Technical Data:

Base: Fine recycled PUR granules and cork
Colour: Brown/black-grey-beige-brown
Fire protection class: Efl (EN 13501)
Impact sound reduction: Up to 19 dB

2 mm

AX36225002

30 m²

1

11

3 mm

AX36225003

20 m²

1

11

5 mm

AX36225005

16 m²

1

11





Fastening

Fastening

Sanding

Coatings

Floor Care

Accessories

Underlayments

Bona U310



Bona U310 is a polyester spunbond fleece that reduces the stress transferred to the subfloor when laying prefabricated parquet, solid parquet and laminate on old parquet or other critical subfloors. Hairline/shrinkage cracks in mineral sub floors can be bridged up to a width of 0.5 mm. Due to its high tear resistance, the decoupling fleece reduces tensions from the subfloor and keeps them away from the subsequent top layer.

Key Benefits:

- Easy to cut
- Stress relieving
- Suitable for use with various Bona adhesives
- DIBt approval

Technical Data:

Base: Polyester spunbond
Colour: Light green
Weight: 160 g/m²
Thickness: 0.8 mm

1 mm

AX36310003

50 m²

1

Bona U340



Bona U340 is a polyester fibre board underlay (4 mm) that reduces the stress transferred to the subfloor when installed prior to the final floor covering e.g. ceramic tiles, natural stone, wooden flooring, etc. Its high compressive strength renders it capable of tolerating high loads (up to 5.0 kN/m²). It is suitable for use in domestic and commercial premises. Additionally, acoustic dampening for all floor types is significantly improved. It is easy to cut, shape and install and is unaffected by dampness and fungal decay.

Key Benefits:

- Reduces subfloor stress
- Bridges cracks/breaks in the subfloor
- Traffic load up to 5 kN/m²
- Dibt approval

Technical Data:

Product/material: Polyester bonded fibre board
Dimensions: 1000 x 600 x 4 mm
Weight: 4 mm = 3.1 kg/m²
Compressive strength: (DIN 53456) 10 N/mm²
Bending strength: (DIN 53453) 2 N/mm²
Tensile strength: (DIN 53457) 6.0 N/mm²
Floor-load capacity: 5.0 kN/m²
Thermal conductivity: 4 mm = λ 0.11 W/(mK)
Thermal resistance: 4 mm = 0.04 m²K/W
Fire resistance class: E (fl) acc. to EN 13501

4 mm

AX36340004

0.6 m²

1

200

Water-based Adhesives

Bona D700



Dispersion-based "white glue" for installing engineered parquet with tongue and groove joints. Moisture resistant and conforms to Class D3 according to EN204.

Key Benefits:

- Quick drying
- Long open time
- Moisture resistant

Technical Data:

Base: 1-comp PVAC
Consumption: 5–30 g/running metre

BD70001100GBBO

0,75 kg

12

500

Bona D705



Hard dispersion-based adhesive, characterised by its strong adhesion properties and longer open time. Suitable for a wide range of parquets.

Key Benefits:

- Extended open time
- Strong adhesion
- Broad functionality

Technical Data:

Base: 1-comp PVAC
Open time: approx. 20 min
Consumption: 850-1250 g/m²

BD70504700M1BO

22 kg

1

24



ЦИКЛЕВОЧНАЯ
КОМПАНИЯ
WWW.TPARKET.RU +7(495) 545-25-85

Bona®



Fastening

Water-based Adhesives

Bona D720



Hard dispersion based adhesive with low water content and very rapid setting properties. Suitable for a wide range of parquet installations. Free from solvents and completely odourless. Firm texture and very easy to spread.

Key Benefits:

- Rapid setting
- Retains trowel pattern
- High strength

Technical Data:

Base: 1-comp PVAC
Open time: Approx. 15 min
Consumption: 850–1250 g/m²

BD72002800M1BO

22 kg

1

24

Bona D750



Dispersion based wet bed adhesive for installing PVC design floors in tile or plank format. Having a long open time and allowing fine adjustments to be made after fitting, makes installation easy and safe. Fibre-reinforced for minimised risk of joint formation.

Key Benefits:

- High shear strength
- Quick and excellent grab
- No venting required, floor coverings can be placed directly

Technical Data:

Base: 1-comp PVAC, fibre-reinforced
Colour: Beige
Application: Notched trowel
Venting time: Approx. 5 min*
Open time: Approx. 30 min*
Consumption: Approx. 200–300 g/m²
 *at 20°C and 50%rH

BD75002200DEBO

6 kg

1

60

BD75002700DEBO

14 kg

32

PU adhesives – Reactive

Bona R200



Liquid repair material for filling hollow spots in parquet floors as well as reattaching loose elements and boards. Once injected the material expands and effectively fills up the hollow space.

Key Benefits:

- Simple solution to a difficult problem
- Excellent adhesion properties
- Contains no water or solvents

Technical Data:

Base: 1-comp PU
Drying time: 4 h

BR20005900M1BO

530 g

6



Fastening

Fastening

Sanding

Coatings

Floor Care

Accessories

PU adhesives – Reactive

Bona R777

Two-component, hard parquet adhesive. Bona R777 has a very long pot life and open time, allowing complex patterns to be laid without stress. Containing no water or solvents, it is particularly suitable for wood species and parquet types sensitive to moisture as well as low/non-absorbent subfloors. Able to withstand very high thrust from wood movement and creates a rigid, stable floor.



Key Benefits:

- Extended pot life and open time for installing complex parquet patterns
- Strong and stabilising
- Allows load after 24 h

Technical Data:

Base: 2-comp PU
Density: 1.5 g/cm³
Colour: Component A: beige
 Component B: brown
Application: Notched trowel
Pot life: Approx. 70 min
Open time: Approx. 110 min
Consumption: 850–1250 g/m

BR77705000M1BO	7 kg	1	60
BR77702700M1BO	14 kg	1	60

Bona R778

Two-component, hard parquet adhesive. Bona R778 has very long open time and particularly good rib stability that simplifies the installation of wooden planks. Containing no water or solvents, it is particularly suitable for wood species and parquet types sensitive to moisture as well as low/non-absorbent subfloors. Able to withstand very high thrust from wood movement and creates a rigid, stable floor.



Key Benefits:

- Good rib stability
- Strong and stabilising
- Allows load after 24 h

Technical Data:

Base: 2-comp PU
Density: 1.7 g/cm³
Colour: Component A: Beige
 Component B: brown
Application: Notched trowel
Pot life: Approx. 40 min
Open time: Approx. 110 min
Consumption: 850–1250 g/m

BR77802400M1BO	10 kg	1	60
----------------	-------	---	----

Silane Adhesives – Reactive

Bona R848

Bona R848 is an ISO 17178 standard elastic, one-component, Silane-based adhesive, suitable for dimensional, stable, multilayered and engineered parquet. Bona R848 reduces tension to the sub floor. The use of a primer is generally not necessary. The adhesive hardens due to a chemical reaction with moisture.



Key Benefits:

- Easy to apply
- Fast initial bonding strength allows load after 24 h
- Good rib stability
- Up to two year shelf life

Technical Data:

Base: 1-comp silane modified
Density: 1.6 g/cm³
Colour: Beige



BR84802800M1BO	15 kg	1	44
BR84805400M1BO	24 kg	1	32
BR84805600M1BO	600 ml	20	36
BR84805800M1BO	2810 ml	4	21
BR84806800M1BO	5400 ml	2	35



ЦИКЛЕВОЧНАЯ
КОМПАНИЯ
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Fastening

Silane Adhesives – Reactive

Bona R848T



Bona R848T is a higher viscous version of Bona R848. It is an ISO 17178 standard elastic, one-component, silane-based adhesive. Best known for its improved rib stability and quick initial bonding strength, Bona R848T can be used for the installation of solid timber floors; including overlay, parquet, blocks and engineered floors. Use with the Bona OptiSpread system for optimal application.

Key Benefits:

- Easy to apply
- Fast initial bonding strength allows load after 24 h
- Up to two year shelf life
- Perfect rip stability, no risk of hollow spots

Technical Data:

Base: 1-comp silane modified
Density: 1.6 g/cm³
Colour: Beige
Application: Notched trowel
Open time: Approx. 30 min
Consumption: 850–1250 g/m²

BR848T5600M1BO	600 ml	20	36
BR848T5700M1BO	1800 ml	6	30
BR848T5800M1BO	2810 ml	4	21
BR848T6800M1BO	5400 ml	2	35
BR848T2800M1BO	15 kg	1	44

Bona R850



Bona R850 is an ISO 17178 standard hard-elastic, one-component, silane-based adhesive for parquet floors (for solid elements in particular). Like conventional adhesives, this hardened adhesive also has the ability to withstand thrust during expansion, while its resistance against shrinkage is very low, thus reducing tension to the subfloor.

Key Benefits:

- A high performance all-rounder
- Fast initial bonding strength allows load after 24 h
- Up to two year shelf life
- More than 10 million m² coverage since 2005
- Possible to use on outside decks
- Direct use on tiles and metal

Technical Data:

Base: 1-comp silane modified
Density: 1.5 g/cm³
Colour: Beige
Application: Notched trowel
Open time: approx. 40 min
Consumption: 850-1500 g/m²

BR85005000M1BO	7 kg	1	60
BR85002800M1BO	15 kg	2	44
BR85006800M1BO	5400 ml	1	35

Bona R850T



Bona R850T is a higher viscous version of Bona R850. It is an ISO 17178 standard hard-elastic, one-component, silane-based adhesive that is specially developed for application using the Bona OptiSpread system, although it can also be applied manually. This adhesive can be used for almost all types of wooden floors - in particular for the installation of solid elements in bigger formats. Like conventional adhesives, this hardened adhesive also has the ability to withstand thrust during expansion, while its resistance against shrinkage is very low, thus reducing tension to the subfloor.

Key Benefits:

- A high performance all-rounder
- Perfect rib stability, no risk of hollow spots
- Up to two year shelf life
- Fast initial bonding strength allows load after 24 h
- Possible to use on outside decks
- Direct use on tiles and metal

Technical Data:

Base: 1-comp silane modified
Density: 1.6 g/cm³
Colour: Beige
Application: Notched trowel
Open time: Approx. 40 min
Consumption: 850–1500 g/m²

BR850T2800GBBO	15 kg	1	44
BR850T5600M1BO	600 ml	20	36
BR850T5700M1BO	1800 ml	6	30
BR850T5800M1BO	2810 ml	4	21
BR850T6800M1BO	5400 ml	2	35



Bona Titan



Bona Titan is a powerful and hard adhesive, containing revolutionary Titanium Technology. Suitable for use on all types of wood floor installations, including oversized elements. Quadruple crosslinking system ensures fast, safe and complete hardening, even under unfavourable conditions.

Key Benefits:

- Extremely good grab for easy installation
- High shear strength
- Allows load after 6 hrs

Technical Data:

Base: 1-comp silane modified
Density: 1.7 g/cm³
Colour: Beige
Application: Notched trowel
Open time: approx. 30 min
Consumption: 850-1500 g/m²

BRTIT02800M1BO

15 kg

1

44

Bona R880



Bona R880 is a strong, elastic construction adhesive based on silane. Contains no plasticisers and can be used to glue many different materials. Specially designed for repair works on silane-bonded floors but also for skirting boards and similar applications.

Key Benefits:

- Quick grab and hardening
- High strength
- Excellent adhesion properties

Technical Data:

Base: 1-comp silane modified
Density: 1.4 g/cm³
Colour: Beige
Application: Adhesive gun
Open time: Approx. 10 min
Application of load: 4–8 h

BR88000300M1BO

330 ml

12

75

Bona OptiSpread



Lightweight adhesive applicator for an upright, fast and ergonomic application of adhesives to residential areas and other smaller locations. Battery driven for high mobility. Comprising a 250 mm wide spreader, it is perfect for the installation of engineered parquet and the innovative construction ensures clean and easy operation. The aluminium body has a Teflon® coated interior as well as sturdy resting legs and base plate. 4 spreaders are included on delivery, 2 fine (approx. 850 g/m²) and 2 large (approx. 1250 g/m²) packed in a convenient transportation bag.

Key Benefits:

- For fast, ergonomic and clean application of adhesives to residential areas
- Reduces adhesive waste, empties the entire adhesive tube
- High quality, non-corrosive body

OptiSpread 2.0	AT32046051	2 810 ml		
OptiSpread 100	AT32046052	5 400 ml		
ACCESSORIES				
Nozzle Adapter	AT32046053	500 mm		
Nozzle Adapter	AT32046054	250 mm		
Thread cap for nozzles	AT32046055			
Spare nozzle 1250 F	AT32046056	250 mm		
Spare nozzle 850 F	AT32046057	250 mm		
Spare nozzle 1250 F	AT32046058	500 mm		
Spare nozzle 1500 F/G	AT32046059	500 mm		
Plastic Caps for nozzles	AT32046060			





Fastening

Fillers & Repair

Bona Gap Master



Bona Gap Master is an acrylic-based mastic for sealing gaps towards skirting boards and thresholds in connection with wooden floors. It can also be used to repair damages and to fill gaps and cracks in the floor.

Key Benefits:

- Permanently elastic (max 15% tolerance)
- High initial and final bonding strength
- Odourless

Technical Data:

Material: Acrylate

Drying time: approx. 18–24 h. Full hardness is achieved after approx. 2–3 days depending on climate and size of gap.

Consumption: Depends on size of the gap.

Type	Article number	Packaging	Pcs/transport package	Package/pallet
RAL 7030	AF4411312500	310 ml	12	60
Dark beech	AF4411311000	310 ml	12	60
Ash/fir	AF4411311100	310 ml	12	60
Dark oak	AF4411311200	310 ml	12	60
White	AF4411311300	310 ml	12	60
Maple	AF4411311400	310 ml	12	60
Light beech	AF4411311500	310 ml	12	60
Light oak	AF4411311600	310 ml	12	60
Cherry	AF4411311700	310 ml	12	60
Bog oak	AF4411311800	310 ml	12	60
Wenge	AF4411311900	310 ml	12	60
Black	AF4411312000	310 ml	12	60
Nut	AF4411312100	310 ml	12	60
Teak	AF4411312200	310 ml	12	60
Reddish exotic wood	AF4411312300	310 ml	12	60



Fastening

Fastening

Sanding

Coatings

Floor Care

Accessories

Application Tools

Type

Article number

Packaging

Pcs/transport
package

Package/
pallet

Bona R580 Trowel



Notched trowel appropriate for applying Bona R590, silane-based damp-proof membrane.

500F (A3)

AT31400280

180 x 150 mm

10


500F (A3)

AT31400380

250 x 150 mm

10

Bona Notched Trowel



Notched trowels for adhesive application.

200F (A2)

AT31413180

180 x 150 mm

10

200F (A2)

AT31413250

250 x 150 mm

10

850F (B3)

AT31401180

180 x 150 mm

10

850G (B6)

AT31402180

180 x 150 mm

10

850G (B6)

AT31402250

250 x 150 mm

10

1000F (B8)

AT31403180

180 x 150 mm

10

1000G (B10)

AT31404180

180 x 150 mm

10

1000G (B10)

AT31304250

250 x 150 mm

10

1250F (B12)

AT31405180

180 x 150 mm

10

1250G (B13)

AT31406180

180 x 150 mm

10

1500F (B14)

AT31409180

180 x 150 mm

10

1500G (B16)

AT31410180

180 x 150 mm

10

Cartridge Applicator



Cartridge Applicator for 310 ml cartridges or 600 ml tubular bags (e.g. Bona R850T).

310 ml

AT32040000

1

600 ml

AT32042000

1

Other Products

Article number

Packaging

Pcs/transport
package

Package/
pallet

Quartz Sand



Fine quartz sand for distribution onto wet R410 and R580. Can also be added to Bona levelling compounds for greater application thickness. Grain size 0,3 – 0,8 mm.

AX36500000

25 kg

1

40



ЦИКЛЕВОЧНАЯ
КОМПАНИЯ
WWW.TPARKET.RU +7 (495) 545-25-85

Bona®



Sanding

The key to great sanding results lies in the perfect combination of machines and abrasives used. Bona's sanding tools not only deliver exceptional results, our systems are also made for maximum efficiency, ergonomics and safety.

With innovations such as dust-free sanding, we always strive to find new ways to improve the craftsman's working environment and process. This year we've pushed the boundaries of innovation by introducing the Bona PowerDrive NEB, the latest addition to the Bona Power Drive range. Used in combination with Bona FlexiSand 1.9, as part of our unique new Bona Brush Technology, now you can achieve even more textures and creative effects.

- | | |
|----------------------|---------------------|
| 1. Dust Free Sanding | 6. Buffing Machines |
| 2. Belt Sanders | 7. Vacuum Cleaners |
| 3. Expansion Sanders | 8. Other Machines |
| 4. Edgers | 9. Abrasives |
| 5. FlexiSand System | |



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

Fastening

Sanding

Coatings

Floor Care

Accessories

Dust Free Sanding

Article number

Packaging

Pcs/transport
packagePackage/
pallet

Bona DCS 70



The Bona DCS 70 is a powerful H-classified vacuum unit for dust-free sanding. Its two-step cyclonic separation and unique filter design effectively contains dust within the machine. Even changing the dust bag can be done completely dust free. With the DCS 70 connected to the sanding machine there is no need to seal off connecting rooms or cover paintings and bookshelves. In addition, it provides a cleaner, healthier working environment, compared to using regular dust bags on the sanding machine.

Key Benefits:

- Dust-free sanding
- Ergonomic design and convenient transportation
- Low power consumption
- Quick and dust free swap of dust bags. Unique seamless dust bag solution using LongoPac

Technical Data:

Weight: 38 kg
Dimensions: 800 × 600 × 1200 mm
Dust holding capacity: 70 L
Motor power: 230 V- 50–60 Hz, 1,4kW
Airflow with 7.5 m hose: 250 m³ per hour
Coarse filter: Conical folded polyester filter, 1 m³
Fine filter: class H 13 (99.996%, 0.3 µm), 0.66 m³
Hose aperture: 35 mm diameter
Hose length: 7.5 m including connection adapters

AMO530005

1

1

Dust Bags LongoPac



LongoPac for Bona DCS 70. 20 metres long. Sold in a set of four.

ASO539001

20 m

1

Adapter Kit 1



Adapter Kit for connecting the Bona DCS 70 to non-Bona machines such as Lägler Hummel, Superhummel, Elf and Profit.

ASO539910

1

Adapter Kit 2



Adapter for connecting the Bona DCS 70 to Lägler Flip.

ASO539920

1



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

Dust Free Sanding

Article number

Packaging

Pcs/transport
packagePackage/
pallet

Bona DCS 25



The Bona DCS 25 is a powerful H-classified vacuum cleaner for dust-free sanding. It can be connected to most Bona sanding machines. It meets the highest requirements for vacuum cleaners within the construction industry today, yet it is easy to transport and bring to site.

Key Benefits:

- Dust-free sanding
- Smaller size for convenient transportation
- Low power consumption
- Electrical outlet with automatic start/stop
- 7,5 m non marking hose

Technical Data:

Weight: 20 kg
Dimensions: 550 × 500 × 1070/830 mm
Dust holding capacity: 25 L
Motor power: 230 V- 50–60 Hz, 1,45 kW
Airflow: 194 m³ per hour

AMO540000

1

1

Fleece Dust Bag

Disposable fleece dust bag for DCS 25.



ASO540001

1

10



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

Belt Sanders

Fastening

Sanding

Coatings

Floor Care

Accessories

Bona Belt HD



Belt Sander that makes big jobs seem small. It is a true heavy-duty machine with tremendous power and very effective. The unique dual-speed pulley system and infinite drum pressure adjustment guarantee optimum sanding quality regardless of wood species. It can be easily disassembled into three parts, and quickly reassembled. Power, reliability and capability are some of the benefits of this effective all-around belt sander. For optimal dust reduction, the Bona Belt HD is compatible with Bona DCS 70.

Key Benefits:

- Heavy weight for powerful sanding
- Dual speed for optimum sanding results
- Easy fitting and changing of paper
- Can fit distressing drums to texture wood floors on site

Technical Data:

Drum width: 200 mm
Sanding belt size: 200 x 750 mm
Motor power: 2.2/3.0/3.7 kW
Total weight: 80/83/85 kg
Drum revolutions: 1850/2050 rpm

200 mm	AMK170000	230 V / 50 Hz	1	3.7 kW
200 mm	AMK170002	230 V / 60 Hz	1	3 kW
200 mm	AMK171010	220 V / 60 Hz	1	3.7 kW
200 mm	AMK172000	230 V / 50 Hz	1	3 kW
200 mm	AMK173000	230 V / 50 Hz	1	2.2 kW

Transport Cart



Transport cart that simplifies transportation of the Bona Belt HD and protects the machine wheels from damage.

ASK6999940006

1

Bona CEE Adapter



Enables the Bona Belt and the Bona DCS 70 to be used with a regular 230 V cable.

ASO903670

1



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

Belt Sanders

Type

Article number

Volt/Hertz

Pcs/transport package

Effect

External Soft Start



External soft-start unit for reducing the potential for fuse breakage. For machines without built in soft- or easy-start systems.

ASO903680

1

Bona Belt



Powerful belt sander with compact design for easy manoeuvring and handling. The Bona Belt takes on any wooden floor and with its easy-start motor, only a 10 Amp fuse is needed for it to run. All adjustments can be made from the top of the machine and the sanding drum is easily changed to another width if needed. The unique drum construction makes changing abrasive belts a job done in seconds. Bona Belt has a highly efficient vacuum unit that minimises dust. For optimal dust reduction, connect it to Bona DCS 70.

Key Benefits:

- Powerful wood floor sander
- Ergonomic design with convenient lifting and lowering of the sanding drum
- Disassembles easily for easier transportation
- Easy-start motor

Technical Data:

Drum width: 200 & 250 mm

Sanding belt size: 200 × 750 mm alt. 250 × 750 mm

Motor power: 1-phase Europe/Asia 2.2 kW

Total weight: 74 kg

Dust discharge: < 2 mg/m³ air

250 mm

AMO110000.3

230 V / 50 Hz

1

2.2 kW

200 mm

AMO110001.3

230 V / 50 Hz

1

2.2 kW

Extra Weight



An extra 7 kilos for the Bona Belt for increased stability and sanding performance.

7 kg

ASO991110

1

Transport Cart



Transport cart that simplifies transportation of the Bona Belt and protects the machine wheels from damage.

ASO995022

1

Bona Belt Lite



The Bona Belt Lite is a compact belt sander able to do great jobs for its size. Designed to provide the perfect combination of efficiency, power and agility. It can be easily disassembled into three parts, and quickly reassembled in a few simple steps. For optimal dust reduction, the Bona Belt Lite is compatible with Bona DCS 70.

Key Benefits:

- Optimal balance between weight and drum pressure
- Superior manoeuvrability
- Easy fitting and changing of paper

Technical Data:

Drum width: 200 mm

Sanding belt size: 200 × 750 mm

Motor power: 2.2 kW

Total weight: 60 kg

Drum revolutions: 2400 rpm

200 mm

AMK175000

230 V / 50 Hz

1

2.2 kW

200 mm

AMK175010

220 V / 60 Hz

1

2.2 kW



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.IPARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

Expansion Sanders

Type

Article number

Volt/Hertz

Pcs/transport package

Effect

Bona Scorpion



Expansion drum sanding machine designed to be a lightweight professional tool that can be easily and very safely operated by any user. Unique electrical power supply safety features such as the "dead man's grip" handle guarantee safe operation. Bona Scorpion is the perfect combination of functionality, reliability, safety and ease of use.

Key Benefits:

- Compact yet effective
- Step-less pressure adjustment
- Easy fitting and changing of paper
- Can fit distressing drums to texture wood floors on site

Technical Data:

Drum width: 200 mm
Sanding belt size: 200 x 480 mm
Motor power: 1.15 kW
Total weight: 45 kg
Drum revolutions: 3300 rpm

200 mm	AMK180000	230 V / 50 Hz	1	1.5 kW
200 mm	AMK180011	115 V / 60 Hz	1	1.5 kW

Bona Scorpion DCS



Delivering the same performance and ease of operation as the Bona Scorpion, the DCS version comes with the attached Dust Care System which operates on an independent switch, and it can also be connected to other machines. Bona Scorpion DCS is the perfect combination of functionality, reliability, safety, ease of use and dust-free sanding.

Key Benefits:

- DCS vacuum on board
- 3-step pressure adjustment
- Easy fitting and changing of paper
- Can fit distressing drums to texture wood floors on site

Technical Data:

Drum width: 200 mm
Sanding belt size: 200 x 480 mm
Motor power: 1.3 kW + 1.2 kW (vacuum unit)
Total weight: 43 kg
Drum revolutions: 3000 rpm

200 mm	AMK185000	230 V / 50 Hz	1	1.3 kW
200 mm	AMK185010	115 V / 60 Hz	1	1.3 kW

Microfiber Dust Bag Large



Disposable Microfiber Dust Bag for belt and expansion sanders.

Key Benefits:

- Rip-resistant
- Reduces airborne dust
- Easy to change

	ASO991011		1	
--	-----------	--	---	--



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

Expansion Sanders

Tynex Distressing Drum



Distressing drums for belt sanders. Metal for rough brushing and Tynex for fine brushing.

195 mm	ASK6099940046	Bona Belt HD	1	
195 mm	ASK2999940046	Bona Scorpion	1	

Metal Distressing Drum



Distressing drums for belt sanders. Metal for rough brushing and Tynex for fine brushing.

195 mm	ASK6099940045	Bona Belt HD	1	
195 mm	ASK2999940045	Bona Scorpion	1	

Edgers

Bona Edge XL



Bona Edge XL (220 mm) is an extremely powerful edge sander. It can be fitted with 'holed discs' or Velcro-backed discs and picks up dust better than most edge sanders on the market. It is equipped with a lamp for better visibility and is easy to operate. For optimal dust reduction, the Bona Edge XL is compatible with Bona DCS 70.

Key Benefits:

- High cut rate
- Easy to handle
- Effective dust pickup

Technical Data:

Disc diameter: 178 mm
Total weight: 14.5 kg
Sanding arm length: 220 mm
Disc speed: 3000 rpm
Dust discharge: < 1 mg/m³ air

220 mm	AMO230009.3	230 V / 50 Hz	1	2.0 kW
--------	-------------	---------------	---	--------

Bona Edge



The compact Bona Edge is an extremely powerful and easily manoeuvrable edge sander. It can be fitted with 'holed discs' or Velcro-backed discs and picks up dust better than most edge sanders on the market. It is equipped with a lamp for better visibility and its shorter sanding arm improves manoeuvrability and reduces strain on arms and hands. For optimal dust reduction, the Bona Edge is compatible with Bona DCS 70.

Key Benefits:

- High cut rate
- Good reachability
- Effective dust pickup

Technical Data:

Disc diameter: 178 mm
Total weight: 14.5 kg
Sanding arm length: 130 mm
Disc speed: 3000 rpm
Dust discharge: < 1 mg/m³ air

130 mm	AMO230018.3	230 V / 50 Hz	1	2.0 kW
--------	-------------	---------------	---	--------



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

Edgers

Type

Article number

Volt/Hertz

Pcs/transport package

Effect

Bona CombiEdge

A lightweight and flexible edge sander. Easily switches between a 120 mm short-arm edger or a 330 mm long-arm sander in just a few simple steps. The 330 mm arm provides excellent reach under deep toe kicks and radiators. The lightweight and highly efficient edge-sanding machine is also fitted with a frontal LED light for better visibility. For optimal dust reduction, the Bona CombiEdge is compatible with Bona DCS 70.

Key Benefits:

- Arm easily replaced for sanding under stairs
- Lightweight construction
- Integrated LED

Technical Data:

Disc diameter: 150 mm
Total weight: Short arm 7.5 kg; Long arm 8.3 kg
Length sanding arm: 120 /330 mm
Disc speed: 3300 rpm
Dust discharge: < 2.0 mg/m³



120 mm	AMK280100	230 V / 50 Hz	1	1.15 kW
120 mm	AMK280010	115 V / 60 Hz	1	1.15 kW
330 mm	AMK281100	230 V / 50 Hz	1	1.15 kW
330 mm	AMK281010	115 V / 60 Hz	1	1.15 kW
120/330 mm	AMK282010	230 V/ 50 Hz	1	1.15 kW
120/330 mm	AMK282100	230 V/ 50 Hz	1	1.15 kW

Bona CombiEdge Stair Support

Attachement to CombiEdge for making sanding of stairs easier by creating stability support.



330 mm	ASK66000030150		1	1
--------	----------------	--	---	---



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

Edgers

Bona DualEdge



Steering sander that is extremely easy to operate due to the counter-rotating 100 mm dual-head discs. The discs deliver forgiving sanding action, stability, high speed and force the dust towards the dust extractor. Bona DualEdge is equipped with a front LED for better illumination of the working area. This revolutionary concept greatly increases working speed. For optimal dust reduction, the Bona DualEdge is compatible with Bona DCS 70.

Key Benefits:

- Counter-rotating dual-head discs
- Sands close to corners – less fine sanding needed
- Lightweight construction

Technical Data:

Disc diameter: 100 mm
Total weight: 9 kg
Length sanding arm: 155 mm
Disc speed: 4500 rpm

155 mm	AMK270000	230 V / 50 Hz	1	1.15 kW
155 mm	AMK270010	115 V / 60 Hz	1	1.15 kW

Microfiber Dust Bag Small



Disposable Microfiber Dust Bag for edge sanders.

Key Benefits:

- Rip-resistant
- Reduces airborne dust
- Easy to change

	ASO992011		2	
--	-----------	--	---	--

FlexiSand System

Bona FlexiSand



A powerful and flexible machine that can be equipped with different drive plates for a wide variety of floor preparation jobs. Its robust construction ensures stable operation, even under heavy load. Bona FlexiSand is compatible with the Bona Power Drive, a unique drive plate that allows powerful, direction-free sanding down to the bare wood. Available with a 1.5 and 1.9 kW motor.

Key Benefits:

- Powerful single-speed motor
- Foldable handle reduces space during transportation
- Large wheels for easy transportation
- Bona Power Drive ready

Technical Data:

Abrasive disc speed: 147 rpm
Motor Power: 1.5/1.9 kW
Total weight: 45 kg
Height/Width/Depth: 1170 mm / 490 mm / 640mm

Ø 407 mm	AMO310002	230 V / 50 Hz	1	1.9 kW
Ø 407 mm	AMO310001	230 V / 50 Hz	1	1,5 kW
Ø 407 mm	AMO310007	220 V / 60 Hz	1	1.9 kW

Extra Weights



For increased power during coarse sanding with the Bona FlexiSand 1.9.

	ASK3199940008	2 x 7 kg	1	
--	---------------	----------	---	--



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

Fastening

Sanding

Coatings

Floor Care

Accessories

FlexiSand System

Type

Article number

Packaging

Pcs/transport
packagePackage/
pallet

Bona Power Drive



The innovative Bona Power Drive, to be used exclusively with the Bona FlexiSand 1.9, sets a new standard in sanding down to the bare wood. Using a direction-free sanding technique, the drive combines excellent performance with easy operation. Four rotating discs sand closely to the walls reducing the need for edge sanding. The geared plate and revolving discs also deliver increased power for excellent performance in bare wood sanding when used in combination with Bona 8700 Ceramic abrasives.

Key Benefits:

- For powerful rotary sanding to bare wood
- Reduces need for edge sanding. Only leaves a 3 cm strip against the wall.
- Delivers a fantastically fine and smooth sanding result
- Failsafe, no risk of drum marks and similar

Technical Data:

Compatible with: Bona FlexiSand 1.5

No. of discs: 4

Disc diam.: 150 mm

Weight: 6.7 kg

Dimensions: 410 mm / 410 mm / 93 mm

Ø 407 mm

ASO312540

4 x Ø 150 mm

1

Bona Quattro Disc



Four-plate disc for an excellent surface finish. Perfect for reducing and smoothing out drum marks and rotational scratches from edger machines. The Bona Quattro Disc will optimise your sanding results and is perfectly balanced for high efficiency combined with smooth end results.

Ø 407 mm

ASO312530

4 x Ø 150 mm

1

Bona Multidisc



With its six-plate construction, the Bona Multidisc creates an exceptionally smooth and flat surface finish. A tool perfect to use before staining or oiling wooden floors with pigmented oil.

Ø 125 mm

ASO312520

6 x Ø 125 mm

1

Replacement Pad Set



Replacement for broken or used pads for the Quattro Disc.

Ø 150 mm

ASO319934

Ø 150 mm

4

Ø 407 mm

ASO319936

6 x Ø 125 mm

6

Bona Pad Drive



The Bona Pad Drive is delivered with the FlexiSand 1.5. A multipurpose tool that can be used to drive different pads and abrasive materials for a large number of applications including oiling, cleaning, buffing and superficial sanding.

Ø 407 mm

ASO312501

6

LED lamp



Two powerful LED lamps for better visibility when working with the Bona FlexiSand 1.5.

ASO319000

1



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

FlexiSand System

Type

Article number

Packaging

Pcs/transport package

Package/pallet

Bona Power Drive NEB



The Bona Power Drive NEB, used exclusively with the Bona FlexiSand 1.9, adds a new dimension to sanding and wire brushing wood floors, using only one tool. The flexible Bona Power Drive NEB makes it possible to change between the traditional sanding discs and specially developed brushes. With its specially designed click-on mount, attachments can be changed in a minute. Using direction-free sanding and brushing techniques, the drive combines excellent performance with easy operation. NEB Discs sold separately.

Key Benefits:

- Flexible - one drive plate for both sanding and brushing jobs.
- Reduces need for edge sanding. Only leaves a 3 cm strip against the wall.
- Delivers a fantastically fine and smooth sanding result
- Failsafe, no risk of drum marks and similar

Technical Data:

Compatible with: Bona FlexiSand 1.9

No. of discs: 4

Disc diam.: 150 mm

Ø 407 mm

ASK3199940991

4 x Ø 150 mm

1

NEB Sanding Disc

Intermediate disc for mounting velcro abrasive discs



Ø 150 mm

ASK3199941010

1

4

NEB Metal Brush

First step in a brushing sequence, for aggressive brushing.



Ø 150 mm

ASK3199941030

1

4

NEB Tynex Brush

Second step in a brushing sequence, smoothes the surface and removes scratches.



Ø 150 mm

ASK3199941020

1

4

Internal Spur Gear

Gear ring for the Bona Flexisand 1.9. Necessary if your Flexisand 1.9 is not already equipped with this.



Ø 407 mm

ASO312082

1

1



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

FlexiSand System

Type

Article number

Packaging

Pcs/transport
package

Package/
pallet

Bona Supraflex



Bona Supraflex is the perfect sanding companion to the Bona Power Drive NEB, helping you with those hard-to-reach areas. It supports all functions of the Bona Power Drive NEB and can fit both sanding discs as well as brushes. M14 tool fixture – easy to change between sanding disc to brushes.

Key Benefits:

- Powerful 1400 W motor
- Stepless speed selection (600-2100 rpm)
- Low height - Easy to reach under staircases, toe kicks and radiators
- Dust cover allows connection to Bona DCS for dust free sanding
- Noise reduction through innovative planetary and angular gears

Technical Data:

Power: 1400 W 230 V – 50/60 Hz
Speed: 600-1200 rpm (stepless)
Tool fixture: M14
Disc diameter: 150 mm
Weight: 2,6 kg

Ø 150 mm

AMF100000

1

1

Cup Brush Metal M14



Cup Brush Metal for use together with Bona SupraFlex sander.

Ø 80 mm

ASF100100

1

1

Ø 120 mm

ASF100200

1

1

Cup Brush Nylon M14



Cup Brush Nylon for use together with Bona SupraFlex sander.

Ø 120 mm

ASF100300

1

1

Bona FlexiVacuum



Bona FlexiVacuum is a part of Bonas Dust free sanding offer, for improved working environment. It is classified in Class M according to EN 60 335-2-69, ensuring that 99,9% or the particles are removed by the filters. Can be mounted on Bona FlexiSand.

Key Benefits:

- Healthier working conditions - M Classified, health hazardous dust EN 60335-2-69.
- Electrical power outlet
- LED- alarm light in case of too low air flow

Technical Data:

Weight: 6kg
Collection capacity (bag): Approx. 10 litres wood dust
Motor: 800 W, 230 V
Air flow: 171 m³/ hour

ASK3199940901

1

1

FlexiVacuum Filter Dust Bag



Filter dust bag - M Class EN 60 335-2-69

ASO994011

1

5



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.TPARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

FlexiSand System

Bona Concrete Disc



Basic drive plate for fitting different types of sanding segments. Magnetic fixing for quick and easy change of segments.

Ø 407 mm

ASO312570

1

Split Segment



Removal of polyurethane, thin adhesive residues, paint.

ASO312582

1

PCD Maxi Segment



Removal of thick adhesive residues, epoxy and carpet foam.

ASO312581

1

Diamond Segment



Removing sinter layers, preparation of concrete surfaces.

ASO319940

5

Buffing Machines

Bona Buffer



Buffing machine for a wide range of applications including fine wood sanding, cutting back grain raise, cleaning etc. Its reliable and asymmetrically placed 1600W motor ensures steady and stable operation. Simple construction and easy to use with fully adjustable handle height and large transportation wheels.

Technical Data:

Motor type: 1.6 kW, 1 phase, 230V/50Hz

Abrasive disc speed: 120 rpm

Total weight: 33 kg

Height / width / depth: XX mm / 440 mm / XX mm

Ø 407 mm

AMC739000B

220-240 V /
50 Hz

1

1.6 kW

Extra Weight

Mount on machine for extra pressure.

5.7 kg

ASC3611478

1



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

Buffing Machines

Drive Disc



With grip hooks for driving pads.

Ø 407 mm

ASC742069

1

Sanding Disc



Sanding disc for attaching double-sided abrasive discs.

Ø 407 mm

ASC742077

1

Quattro Disc



Four-plate sanding disc for Bona Buffer.

Ø 407 mm

ASC742080

4 x Ø 150 mm

1

Vacuum Unit ASO5



Vacuum unit for attachment on the Bona Buffer.

Technical Data:

Vacuum: 250 mbar

Dust holding capacity: 4.5 litres

Noise level: 62 dBA

Weight: 4.8 kg

Height/Width/Depth: 57 / 29 / 28 cm

ASC780920B

230 V / 50 Hz

1

1.1 kW

Vacuum Sealing Ring



Dust skirt for Bona Buffer to prevent dust escape.

Ø 407 mm

ASC74765

1

Dust Bag – Paper



Disposable paper dust bag.

ASC25430

1

Dust Bag – Cloth



Reusable cloth filter bag.

ASC025435

1



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

Buffing Machines

Bona Mini Buffer



Single-speed buffing machine for basic buffing and superficial sanding of finished surfaces. Smooth running and features an anti-vibration system for ease of use. The handle can be lowered for use under stairs and tables.

Technical Data:

Weight: 13 kg

Ø 300 mm

AMC718010

240 V / 50–60
Hz

1

290 W

Drive Disc



Drive disc for Bona Mini Buffer.

Ø 300 mm

ASC718070

1

Vacuum Cleaners

Bona S20



A powerful, easy to manoeuvre vacuum cleaner with large a dust container. Can be connected to the Bona Buffer with a 4 m hose for effective dust removal during sanding.

Technical Data:

Dust container: 10 L

Hose length: 4 m

Cable length: 10 m

Weight: 10 kg

AMC020000

230 V / 50 HZ

1

1.1 kW

Hitachi CV 300



Lightweight and powerful vacuum cleaner for cleaning of hard floors, carpets, furniture etc.

Technical Data:

Dust container: 10 L

Hose length: 4 m

Cable length: 10 m

Weight: 10 kg

AM45001000

230 V / 50 Hz

1

1.3 kW



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Machines

Fastening

Sanding

Coatings

Floor Care

Accessories

Other Machines

Type

Article number

Volt/Hertz

Pcs/transport package

Effect

Fein MultiMaster Start MSX 636

Fein MultiMaster Start MSX 636 – suitable for many applications like sanding, cutting and scraping.

Key Benefits:

- Ideal for sanding tight corners
- Attached tool can turn fully around drive shaft
- Ergonomical design and lightweight

Technical Data:

Speed: 11 000–21 000 rpm

Weight: 1.2 kg



AM44008000

230 V / 50 Hz

1

250 W

Fein MultiMaster saw blades

Saw blades and accessories for Fein MultiMaster:



80 mm	AS44008003		2	
85 mm, cropped	AS44008009		2	
63 mm, with diamonds	AS44008010		2	
65 mm, E-Cut precision	AS44008014		2	
35 mm, E-Cut	AS44008015		1	

Power Stripper



Can be operated either by hand or as a floor stripper with extension handle. Easy operation by the use of a foot switch. Adjustable hand-grips for easy fit. For removing bonded floor coverings on foam, textile, parquet, semi-flexible tiles or PVC.

Technical Data:

Working width: 210 mm

Power: 2.0 kW

Oscillations: 6500 U/min

Weight: 12.8 kg

Noise level: 85 dB (A)

AM43021000

1



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Abrasives

Superior – Ceramic Mix

Dimension

Grit

Article number

Packaging

Pcs/transport package

Superior abrasive made of ceramic grits for easy removal of hard lacquers, carpet residue and for flattening highly uneven timber. Together with the smoother Bona 8300 Series, it creates an optimal system for high sanding performance combined with an excellent surface finish. The ceramic aluminium oxide grits used on the abrasives are close to diamonds in hardness ensuring extremely long-lasting abrasives with maintained aggressiveness. Polyester cloth backing for outstanding strength and dimensional stability. Discs have Velcro backing for simple fitting of abrasives.

Key Benefits:

- Developed exclusively for wooden floors
- For heavy-duty sanding applications
- Superior durability
- Extreme aggression

Bona 8700 Belt



200 x 750 mm

Grit 36

AAS469500363

1

1

200 x 750 mm

Grit 50

AAS469500503

1

1

250 x 750 mm

Grit 36

AAS469600363

1

1

250 x 750 mm

Grit 50

AAS469600503

1

1

Bona 8700 Roll



203 mm x 10 m

Grit 36

AAS470700361

1

1

203 mm x 10 m

Grit 50

AAS470700501

1

1

254 mm x 10 m

Grit 36

AAS470800361

1

1

254 mm x 10 m

Grit 50

AAS470800501

1

1

305 mm x 10 m

Grit 36

AAS470900361

1

1

305 mm x 10 m

Grit 50

AAS470900501

1

1

Bona 8700 Ceramic Disc



Ø 100 mm

Grit 36

AAS472800365

1

25

Ø 100 mm

Grit 50

AAS472800505

1

25

Ø 125 mm

Grit 36

AAS471600365

1

25

Ø 125 mm

Grit 50

AAS471600505

1

25

Ø 150 mm

Grit 36

AAS471700365

1

25

Ø 150 mm

Grit 50

AAS471700505

1

25

Ø 178 mm

Grit 36

AAS471800365

1

25

Ø 178 mm

Grit 50

AAS471800505

1

25



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-80

Bona®



Sanding – Abrasives

Premium – Zircon Mix

Dimension

Grit

Article number

Packaging

Pcs/transport package

Premium abrasive made of an optimal blend of zirconium and silicon carbide for a perfect balance between aggressiveness and surface finish. The Bona 8300 abrasives are of very high durability and have an antistatic coating which impedes clogging and ensures cooler and longer runtime as well as better dust extraction. The character of the grit material is such that new sharp points are created during use, ensuring maintained aggressiveness throughout its lifetime. Lasts up to five times longer than conventional aluminium oxide abrasives. Discs have Velcro backing for simple fitting of abrasives.

Key Benefits:

- Unique composition developed exclusively for wooden floors
- Antistatic properties for minimised clogging and optimal dust extraction
- Very high durability
- High heat resistance

Bona 8300 Antistatic Belt



200 x 750 mm	Grit 24	AAS467700243	1	10
200 x 750 mm	Grit 36	AAS467700363	1	10
200 x 750 mm	Grit 40	AAS467700403	1	10
200 x 750 mm	Grit 60	AAS467700603	1	10
200 x 750 mm	Grit 80	AAS467700803	1	10
200 x 750 mm	Grit 100	AAS467701003	1	10
200 x 750 mm	Grit 120	AAS467701203	1	10
200 x 750 mm	Grit 150	AAS467701503	1	10
250 x 750 mm	Grit 24	AAS467800243	1	10
250 x 750 mm	Grit 36	AAS467800363	1	10
250 x 750 mm	Grit 40	AAS467800403	1	10
250 x 750 mm	Grit 60	AAS467800603	1	10
250 x 750 mm	Grit 80	AAS467800803	1	10
250 x 750 mm	Grit 100	AAS467801003	1	10
250 x 750 mm	Grit 120	AAS467801203	1	10

Bona 8300 Antistatic Sleeve



200 x 551 mm	Grit 24	AAS467600243	1	10
200 x 551 mm	Grit 36	AAS467600363	1	10
200 x 551 mm	Grit 40	AAS467600403	1	10
200 x 551 mm	Grit 60	AAS467600603	1	10
200 x 551 mm	Grit 80	AAS467600803	1	10
200 x 551 mm	Grit 100	AAS467601003	1	10
200 x 551 mm	Grit 120	AAS467601203	1	10



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Abrasives

Premium – Zircon mix

Bona 8300 Antistatic Roll



Dimension	Grit	Article number	Packaging	Pcs/transport package
203 mm x 25 m	Grit 24	AAS466300241	1	1
203 mm x 25 m	Grit 36	AAS466300361	1	1
203 mm x 25 m	Grit 40	AAS466300401	1	1
203 mm x 25 m	Grit 60	AAS466300601	1	1
203 mm x 25 m	Grit 80	AAS466300801	1	1
203 mm x 25 m	Grit 100	AAS466301001	1	1
203 mm x 25 m	Grit 120	AAS466301201	1	1
254 mm x 25 m	Grit 24	AAS466400241	1	1
254 mm x 25 m	Grit 36	AAS466400361	1	1
254 mm x 25 m	Grit 40	AAS466400401	1	1
254 mm x 25 m	Grit 60	AAS466400601	1	1
254 mm x 25 m	Grit 80	AAS466400801	1	1
254 mm x 25 m	Grit 100	AAS466401001	1	1
254 mm x 25 m	Grit 120	AAS466401201	1	1
254 mm x 25 m	Grit 220	AAS466402201	1	1



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Abrasives

Premium – Zircon Mix

Dimension

Grit

Article number

Packaging

Pcs/transport package

Bona 8300 Antistatic Disc



Ø 100 mm

Grit 36

AAS472700365

1

25

Ø 100 mm

Grit 60

AAS472700606

1

50

Ø 100 mm

Grit 80

AAS472700806

1

50

Ø 100 mm

Grit 100

AAS472701006

1

50

Ø 100 mm

Grit 120

AAS472701206

1

50

Ø 125 mm

Grit 60

AAS471200606

1

50

Ø 125 mm

Grit 80

AAS471200806

1

50

Ø 125 mm

Grit 100

AAS471201006

1

50

Ø 125 mm

Grit 120

AAS471201206

1

50

Ø 150 mm

Grit 24

AAS467500245

1

25

Ø 150 mm

Grit 36

AAS467500365

1

25

Ø 150 mm

Grit 40

AAS467500406

1

50

Ø 150 mm

Grit 60

AAS467500606

1

50

Ø 150 mm

Grit 80

AAS467500806

1

50

Ø 150 mm

Grit 100

AAS467501006

1

50

Ø 150 mm

Grit 120

AAS467501206

1

50

Ø 150 mm

Grit 24

AAS470600245

1

25

Ø 150 mm

Grit 36

AAS470600365

1

25

Ø 150 mm

Grit 40

AAS470600406

1

50

Ø 150 mm

Grit 60

AAS470600606

1

50

Ø 150 mm

Grit 80

AAS470600806

1

50

Ø 150 mm

Grit 100

AAS470601006

1

50

Ø 150 mm

Grit 120

AAS470601206

1

50

Ø 178 mm

Grit 24

AAS467400245

1

25

Ø 178 mm

Grit 36

AAS467400365

1

25

Ø 178 mm

Grit 40

AAS467400406

1

50

Ø 178 mm

Grit 60

AAS467400606

1

50

Ø 178 mm

Grit 80

AAS467400806

1

50

Ø 178 mm

Grit 100

AAS467401006

1

50

Ø 178 mm

Grit 120

AAS467401206

1

50

Ø 200 mm

Grit 24

AAS471100245

1

25

Ø 200 mm

Grit 36

AAS471100365

1

25

Ø 200 mm

Grit 40

AAS471100406

1

50

Ø 200 mm

Grit 60

AAS471100606

1

50

Ø 200 mm

Grit 80

AAS471100806

1

50

Ø 200 mm

Grit 100

AAS471101006

1

50

Ø 200 mm

Grit 120

AAS471101206

1

50



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Abrasives

Standard – Aluminium Oxide

Dimension

Grit

Article number

Packaging

Pcs/transport package

Standard abrasive belts of aluminium oxide which produces a very fine surface finish. Strong cotton backing for high durability and dimensional stability. Compared to conventional aluminium oxide abrasives, the Bona 8500 Series stands out as a highly durable and good-value alternative.

Key Benefits:

- Exceptional surface finish
- Open coat for cooler sanding
- High durability

Bona 8500 Aluminium Oxide Belt



200 mm x 750 mm	Grit 16	AAS468000163	1	10
200 mm x 750 mm	Grit 24	AAS468000243	1	10
200 mm x 750 mm	Grit 36	AAS468000363	1	10
200 mm x 750 mm	Grit 40	AAS468000403	1	10
200 mm x 750 mm	Grit 50	AAS468000503	1	10
200 mm x 750 mm	Grit 60	AAS468000603	1	10
200 mm x 750 mm	Grit 80	AAS468000803	1	10
200 mm x 750 mm	Grit 100	AAS468001003	1	10
200 mm x 750 mm	Grit 120	AAS468001203	1	10
250 mm x 750 mm	Grit 16	AAS468200163	1	10
250 mm x 750 mm	Grit 24	AAS468200243	1	10
250 mm x 750 mm	Grit 36	AAS468200363	1	10
250 mm x 750 mm	Grit 40	AAS468200403	1	10
250 mm x 750 mm	Grit 50	AAS468200503	1	10
250 mm x 750 mm	Grit 60	AAS468200603	1	10
250 mm x 750 mm	Grit 80	AAS468200803	1	10
250 mm x 750 mm	Grit 100	AAS468201003	1	10
250 mm x 750 mm	Grit 120	AAS468201203	1	10

Bona 8500 Aluminium Oxide Sleeve



200 x 551 mm	Grit 16	AAS467900163	1	10
200 x 551 mm	Grit 24	AAS467900243	1	10
200 x 551 mm	Grit 36	AAS467900363	1	10
200 x 551 mm	Grit 40	AAS467900403	1	10
200 x 551 mm	Grit 50	AAS467900503	1	10
200 x 551 mm	Grit 60	AAS467900603	1	10
200 x 551 mm	Grit 80	AAS467900803	1	10
200 x 551 mm	Grit 100	AAS467901003	1	10
200 x 551 mm	Grit 120	AAS467901203	1	10



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Abrasives


Standard – Silicon Carbide

Dimension	Grit	Article number	Packaging	Pcs/transport package
-----------	------	----------------	-----------	-----------------------

Bona 8100 Silicon Carbide Disc




Ø 100 mm	Grit 36	AAS472600365	1	25
Ø 100 mm	Grit 60	AAS472600606	1	50
Ø 100 mm	Grit 80	AAS472600806	1	50
Ø 100 mm	Grit 100	AAS472601006	1	50
Ø 100 mm	Grit 120	AAS472601206	1	50



Ø 150 mm	Grit 16	AAS466900165	1	25
Ø 150 mm	Grit 24	AAS466900245	1	25
Ø 150 mm	Grit 36	AAS466900365	1	25
Ø 150 mm	Grit 40	AAS466900406	1	50
Ø 150 mm	Grit 50	AAS466900506	1	50
Ø 150 mm	Grit 60	AAS466900606	1	50
Ø 150 mm	Grit 80	AAS466900806	1	50
Ø 150 mm	Grit 100	AAS466901006	1	50
Ø 150 mm	Grit 120	AAS466901206	1	50
Ø 150 mm	Grit 150	AAS466901506	1	50



Ø 150 mm	Grit 36	AAS468400365	1	25
Ø 150 mm	Grit 40	AAS468400406	1	50
Ø 150 mm	Grit 50	AAS468400506	1	50
Ø 150 mm	Grit 60	AAS468400606	1	50
Ø 150 mm	Grit 80	AAS468400806	1	50
Ø 150 mm	Grit 100	AAS468401006	1	50
Ø 150 mm	Grit 120	AAS468401206	1	50



Ø 178 mm	Grit 16	AAS467100165	1	25
Ø 178 mm	Grit 24	AAS467100245	1	25
Ø 178 mm	Grit 36	AAS467100365	1	25
Ø 178 mm	Grit 40	AAS467100406	1	50
Ø 178 mm	Grit 50	AAS467100506	1	50
Ø 178 mm	Grit 60	AAS467100606	1	50
Ø 178 mm	Grit 80	AAS467100806	1	50
Ø 178 mm	Grit 100	AAS467101006	1	50
Ø 178 mm	Grit 120	AAS467101206	1	50

Fastening

Sanding

Coatings

Floor Care

Accessories



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Abrasives

Standard – Silicon Carbide



Dimension	Grit	Article number	Packaging	Pcs/transport package
Ø 200 mm	Grit 16	AAS466600165	1	25
Ø 200 mm	Grit 24	AAS466600245	1	25
Ø 200 mm	Grit 36	AAS466600365	1	25
Ø 200 mm	Grit 40	AAS466600406	1	50
Ø 200 mm	Grit 50	AAS466600506	1	50
Ø 200 mm	Grit 60	AAS466600606	1	50
Ø 200 mm	Grit 80	AAS466600806	1	50
Ø 200 mm	Grit 100	AAS466601006	1	50
Ø 200 mm	Grit 120	AAS466601206	1	50
Ø 200 mm	Grit 150	AAS466601506	1	50

Standard abrasive of silicon carbide, also known as carborundum, a very hard mineral that creates new sharp points when worn ensuring maintained aggressiveness during its lifetime. This property and an open coat ensures cool running on high speed machines such as edge sanders.

Key Benefits:

- Maintained aggression when worn
- Open coat for cool sanding
- High durability

Bona 8100 Silicon Carbide Roll



203 mm x 25 m	Grit 16	AAS466000161	1	1
203 mm x 25 m	Grit 24	AAS466000241	1	1
203 mm x 25 m	Grit 36	AAS466000361	1	1
203 mm x 25 m	Grit 40	AAS466000401	1	1
203 mm x 25 m	Grit 50	AAS466000501	1	1
203 mm x 25 m	Grit 60	AAS466000601	1	1
203 mm x 25 m	Grit 80	AAS466000801	1	1
203 mm x 25 m	Grit 100	AAS466001001	1	1
203 mm x 25 m	Grit 120	AAS466001201	1	1

Bona 8100 Double-sided Disc



Ø 407 mm	Grit 16	AAS466800163	1	10
Ø 407 mm	Grit 24	AAS466800243	1	10
Ø 407 mm	Grit 36	AAS466800363	1	10
Ø 407 mm	Grit 40	AAS466800403	1	10
Ø 407 mm	Grit 60	AAS466800603	1	10
Ø 407 mm	Grit 80	AAS466800803	1	10
Ø 407 mm	Grit 100	AAS466801003	1	10
Ø 407 mm	Grit 120	AAS466801203	1	10



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Abrasives

Fastening

Sanding

Coatings

Floor Care

Accessories

Pads

Type

Article number

Packaging

Package/ pallet

Colour coding for field of use

Smooth



Rough

White – backing for sanding screen. Can also be used for buffing polish.

Tan (beige) – for polishing

Red – for daily cleaning

Green – for periodic cleaning and oil maintenance

Brown – for oil application

Black – for heavy duty cleaning and polish stripping

Pads

Type

Article number

Packaging

Package/ pallet

Bona Superpad 407 mm

Thick pad for Bona FlexiSand 1.5 and Bona Buffer.



White	AAS867300058	Ø 407 mm x 25 mm	5
Tan	AAS867300038	Ø 407 mm x 25 mm	5
Red	AAS867300048	Ø 407 mm x 25 mm	5
Green	AAS867300028	Ø 407 mm x 25 mm	5
Brown	AAS867300068	Ø 407 mm x 25 mm	5
Black	AAS867300018	Ø 407 mm x 25 mm	5

Bona Superpad 280 mm

Pad for Bona Mini Buffer.



White	AA68041000	Ø 280 mm x 25 mm	5
Tan	AA68042000	Ø 280 mm x 25 mm	5
Red	AA68043000	Ø 280 mm x 25 mm	5

Bona Superpad

Incl. EAN code

Thick pad for Bona FlexiSand 1.5 and Bona Buffer.



White	AAS68011000	Ø 407 mm x 25 mm	5
Tan	AAS68012000	Ø 407 mm x 25 mm	5
Green	AAS68013000	Ø 407 mm x 25 mm	5
Black	AAS68014000	Ø 407 mm x 25 mm	5

Bona Pad 407 mm

Thin pad for Bona FlexiSand 1.5 and Bona Buffer.



White	AA68001000	Ø 407 mm x 8 mm	10
Tan	AA68002000	Ø 407 mm x 8 mm	10
Green	AA68003000	Ø 407 mm x 8 mm	10
Black	AA68004000	Ø 407 mm x 8 mm	10







**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Abrasives

Pads	Type	Article number	Packaging	Package/ pallet	
<div>Bona Pad 200 mm</div> <div></div>	Pad for Lägler Trio.				
	White	AA68053000	Ø 200 mm x 8 mm		
	Tan	AA68052000	Ø 200 mm x 8 mm		
	Red	AA68055000	Ø 200 mm x 8 mm		
	Green	AA68054000	Ø 200 mm x 8 mm		
<div>Bona Wool Pad</div> <div></div>	Pad for Bona FlexiSand 1.5 and Bona Buffer. The pad is made of genuine sheep wool for application of oil and polishing of oiled or waxed floors. Wool produces higher heat towards the surface compared to synthetic pads, which improves the penetration of oil into the wood and accelerates the drying process. Contains natural lanolin (wool wax) for a satin finish. Highly recommended for Bona Oils.				
	Key Benefits: <ul style="list-style-type: none">• 100% wool pad				
		AA68071000	Ø 407 mm x 8 mm	8	
<div>Microfiber Pad</div>	Cleaning and polishing pad for Bona Mini Buffer.				
		ASC718906	Ø 300 mm	1	
Scrad Pads	Dimension	Grit	Article number	Packaging	Pcs/transport package
<div>Bona Scrad Pad</div> <div></div>	Abrasive pad for Bona FlexiSand 1.5 and Bona Buffer. Used together with a Bona Scrad Wing it forms a unique abrasive system developed for cutting back grain raise between coats of finish. Minimises scratches.				
	Ø 407 mm x 8 mm	Grit 320	AAS854303208		5
	Ø 330 mm x 8 mm	Grit 320	AA970740		5
<div>Bona Scrad Wing</div> <div></div>	Delta shaped abrasive with Velcro backing for use together with the Bona Scrad Pad. Attach 1–2 wings.				
	Delta	Grit 120	AAS468601206		50
	Delta	Grit 150	AAS468601506		50
	Delta	Grit 220	AAS468602206		50





Sanding – Abrasives

Screens

Dimension

Grit

Article number

Packaging


Pcs/transport package

Abrasive screen for surface preparation of wooden floors prior to coating and for cutting back grain raise after coating. High durability and low grit loss. Its open mesh structure impedes clogging and improves dust extraction.


Key Benefits:

- Non-Clogging
- Open mesh structure for improved dust extraction
- Double-Sided

Bona Sanding Screen, double-sided



Ø 407 mm	Grit 60	AAS867100603	1	10
Ø 407 mm	Grit 80	AAS867100803	1	10
Ø 407 mm	Grit 100	AAS867101003	1	10
Ø 407 mm	Grit 120	AAS867101203	1	10
Ø 407 mm	Grit 150	AAS867101503	1	10
Ø 407 mm	Grit 180	AAS867101803	1	10
Ø 407 mm	Grit 220	AAS867102203	1	10



Ø 407 mm	Grit 60	AAS67012060	1	10
Ø 407 mm	Grit 80	AAS67012080	1	10
Ø 407 mm	Grit 100	AAS67012100	1	10
Ø 407 mm	Grit 120	AAS67012120	1	10



Ø 280 mm	Grit 80	AAS872000803	1	10
Ø 280 mm	Grit 100	AAS872001003	1	10
Ø 280 mm	Grit 120	AAS872001203	1	10



Ø 200 mm	Grit 80	AAS903700808	1	30
Ø 200 mm	Grit 100	AAS903701008	1	30
Ø 200 mm	Grit 120	AAS903701208	1	30
Ø 200 mm	Grit 150	AAS903701508	1	30

Fastening

Sanding

Coatings

Floor Care

Accessories



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Abrasives

Diamond Abrasives

Bona Diamond Abrasive Disc



Made using the hardest sanding agents in the world, Bona Diamond Abrasives are unique, delivering unparalleled sanding efficiency, durability and surface smoothness – whether sanding on bare wood or in preparation for recoating. Because the diamond grits are hard but not sharp, the result after fine sanding is a smooth, virtually scratch-free surface.

Bona Diamond Abrasives last up to 15 times longer than competing screen or multihole sanding discs and deliver consistent performance, even after 100 m² of sanding. And thanks to its unmatched hardness, each disc maintains its sanding performance throughout its lifetime.

Key Benefits:

- Longer lasting
- Perfect evenness
- Better surface
- Safe recoating

Ø 150 mm	Grit 80	AAS472000808	1	8
Ø 150 mm	Grit 120	AAS472001208	1	8
Ø 125 mm	Grit 240	AAS471902408	1	12
Ø 150 mm	Grit 240	AAS472002408	1	8

Bona Intermediate Pad



A pressure-equalizing foam pad that has the ability to follow the contours of the surface.

Ø 125 mm		AAS472102408	1	3
Ø 150 mm		AAS472200008	1	4

Bona Cleaning Pad



Strong fibre-weave disc for picking up residual dust after sanding with diamond abrasives. Suitable cleaning method for smaller areas.

Ø 125 mm		AAS472300008	1	12
Ø 150 mm		AAS472400008	1	8

Abrasives Delta

Delta Abrasive Paper



For Fein and Bosch.

82 x 82 x 82	Grit 40	AAS872100406	1	50
82 x 82 x 82	Grit 60	AAS872100606	1	50
82 x 82 x 82	Grit 80	AAS872100806	1	50



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sanding – Abrasives

Abrasives

Dimension

Grit

Article number

Packaging

Pcs/transport package

Bona Net Ceramic



The Bona Net Ceramic is mainly intended to be used for orbital or rotary sanders, such as Supraflex SE 14-2 or similar. It can also be used attached to Bona Power Drive for medium sanding or removal of joint filler.

Technical data

Grit type: Ceramic aluminium oxide

Grit range: 80

Size: 150 mm

Backing: Knitted fabric

Coating: Electrostatic

Bonding: Resin over resin

Key Benefits:

- Minimal clogging
- Good dust extraction
- Very high removal rate
- Independent on machine hole system

Ø 150 mm

Grit 80

AAS473200806

1

50

Bona Net Alox



The Bona Net Alox is mainly intended to be used for orbital or rotary sanders, such as Supraflex SE 14-2 or similar. It can also be used attached to Bona Power Drive for fine and medium sanding.

Technical data

Grit type: White Aluminium oxide

Grit range: 80, 100 and 120

Size: 150 mm

Backing: Knitted fabric

Coating: Electrostatic

Bonding: Resin over resin

Key Benefits:

- Minimal clogging
- Good dust extraction
- High removal rate
- Independent on machine hole system

Ø 150 mm

Grit 80

AAS473300806

1

50

Ø 150 mm

Grit 100

AAS473301006

1

50

Ø 150 mm

Grit 120

AAS473301206

1

50

Fastening

Sanding

Coatings

Floor Care

Accessories



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Coatings

Regardless of the property that is important to you, be it shine, colour, slip resistance or durability, Bona has the ideal surface treatment for all types of wooden floors. Since the 1970s, we have been the world's pioneer in waterborne finishes, providing low-VOC, solvent-free solutions for every flooring need.

Bona continues to drive the development of waterborne lacquers and the latest addition, Bona Mega ONE, is designed to help and simplify the contractors work process making it a reliable partner for everyday use.

On the following pages, you will discover all the surface treatments you need to create beautiful, durable and easy-to-manage wooden floors.

- | | |
|----------------------------|----------------------------|
| 1. Primers | 6. Oils – Outdoor |
| 2. Lacquers | 7. Fillers & Repair |
| 3. Sportive System | 8. Resilient System |
| 4. Oils – Wear Treatment | 9. Resilient - Maintenance |
| 5. Oils – Effect Treatment | |



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Primers

Article number

Packaging

Pcs/transport package

Package/pallet

Bona White



Primer producing a white tint look where the intensity can be controlled by applying it in one or more layers. Applied in a single layer it typically preserves the impression of raw, untreated wood. For a truly white impression, apply two or more layers. Its highly forgiving formula is designed for easy roller application.

Key Benefits:

- White tint look
- Impedes wood yellowing
- Easy roller application

Technical Data:

Base: Acrylate/polyurethane
Category: Waterborne 1-comp
Drying time: 1-2 h between coats
Applications: 1-3
Application tools: Bona Roller
Coverage: 10-12 m²/L

WB250613001

1 L

10

50

WB250620001

5 L

3

44

Bona Natural



Bona Natural Primer is designed to preserve/create the natural appearance of unfinished wood. Overcoat with Bona Traffic Natural lacquer for a truly 'unfinished' look, combined with a highly durable surface. It is quick drying and with good abrasion qualities.

Key Benefits:

- Retains the look of pure wood
- Easy roller application
- Good abrasion qualities

Technical Data:

Base: Acrylate/polyurethane
Category: Waterborne 1-comp
Drying time: 1-2 h between coats
Application: 1-2
Tools: Bona Roller
Coverage: 8-10 m²/L

WB251613001

1 L

12

50

WB251620001

5 L

3

44

Bona Classic



Provides a well-bodied surface. It creates a soft, flexible film that reduces the potential effects of side bonding and its forgiving application properties make it suitable for practically all types of wood. Bona Classic is non-yellowing.

Key Benefits:

- Light colouration
- All types of wood
- Reduces side-bonding effects
- Easy roller application

Technical Data:

Base: Acrylate
Category: Waterborne 1-comp
Drying time: 1-2 h between coats
Application tools: Bona Roller
Coverage: 8-10 m²/L

WB200013003

1 L

10

50

WB200020012

5 L

3

44

Bona Intense



Excellent abrasion properties. Highly suitable for floors with underfloor heating and/or moving floors such as end grain or plank floors. Suitable on practically all types of wood and especially on tropical wood.

Key Benefits:

- Medium colouration
- All wood, tropical wood
- First choice for underfloor heating
- Easy roller application

Technical Data:

Base: Polyurethane
Category: Waterborne 1-comp
Drying time: 1-2 h between coats
Applications: 1
Application tools: Bona Roller
Coverage: 8-10 m²/L

WB250020001

5 L

3

44





Coatings | Wood

Primers

Bona Amber



Excellent abrasion properties. Highly suitable for floors with underfloor heating and/or moving floors such as end grain or plank floors. Suitable for oak and darker types of wood including tropical species.

Key Benefits:

- Rich colouration
- Oak, dark, tropical wood
- Good for underfloor heating
- Easy roller application

Technical Data:

Base: Polyurethane
Category: Waterborne 1-comp
Drying time: 1–2 h between coats
Application tools: Bona Roller
Coverage: 8–10 m²/L

WB255020001

5 L

3

44

Bona Quick



A high viscous primer with a gel-like consistency. Use as a first layer on untreated wood, without following abrasion. Use between coats of finish, to reduce abrasion scratches and fill small irregularities for a flawless end-finish.

Key Benefits:

- Very light colouration
- Quick drying gel
- Reduces scratches
- First layer and/or in-between
- Easy trowel application

Technical Data:

Base: Acrylate/polyurethane
Category: Waterborne 1-comp
Drying time: 20–30 min between coats
Applications: 1–3
Application tools: Stainless steel trowel
Coverage: 25–35 m²/L and application

WB074002002

5 L

1

Bona Decor Paint



Bona Decor Paint is a waterborne paint with ultra-hide properties, specially developed for wooden floors. It covers in 1-2 coats and establishes an excellent background before being sealed with Bona's waterborne lacquer.

Key Benefits:

- Excellent hiding
- Quick dry
- Easy application

Technical Data:

Base: Polyurethane
Category: Waterborne 1-comp
Drying time: 2-3 h
Application tools: Bona Roller (5 mm)
Coverage: 12–15 m²/L and application

Black

WC470120001

5 L

1

White

WC490120001

5 L

1

Light Grey

WC472220001

5 L

1

Dark Grey

WC474220001

5 L

1



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Lacquers

Type

Article number

Packaging

Pcs/transport
package

Package/
pallet

Bona Traffic HD

The world's toughest and fastest drying finish for wooden floors exposed to extreme wear. You can walk on it after just 12 hours. Used in hotels, restaurants and airports worldwide, where short downtime is essential. Waterbased and very low VOC and odor. Non-yellowing.

Key Benefits:

- The ultimate choice
- Superior protection for commercial and public areas
- Extra fast, allows full traffic after just 12 hours
- Very low VOC and odour

Technical Data:

Base: Polyurethane

Category: Waterborne 2-comp

Drying time: 2–3 h between coats

Application tools: Bona Roller

Coverage: 8–10 m²/L and application

- Complies to EN14904:2006 and DIN 18032:2 (suitable friction for sports floors)

- EN 71:3 compliant



Silk Matt	WT155346001	4.95 L	3	36
Matt	WT155646001	4.95 L	3	36
Extra Matt	WT155946001	4.95 L	3	36
Hardener	WH330045001	0.40 L	3	

Bona Traffic HD Anti Slip

Adds the highest standard of friction in areas where it's needed the most – like stairs, nurseries and kitchens. Superb performance against wet spills.

Key Benefits:

- Increases protection from accidental slips (R9)
- Ready to use, no mixing required, safe results
- Very low VOC

Technical Data:

Base: Polyurethane

Category: Waterborne 2-comp

Drying time: 2–3 h between coats

Application tools: Bona Roller

Coverage: 8–10 m²/lit and application



WT153946001

4.95 L

3

36

Bona Traffic

The classic since 1998, with super durability for any area where high wear resistance is needed. Easy to maintain and non-yellowing. Good for both untreated wood and prefinished parquet.

Key Benefits:

- Superior protection for commercial and public areas
- Natural appearance
- Low VOC

Technical Data:

Base: Polyurethane

Category: Waterborne 2-comp

Drying time: 3–4 h between coats

Application tools: Bona Roller

Coverage: 8–10 m²/L and application

- Complies to EN14904:2006 and DIN 18032:2 (suitable friction for sports floors)

- EN 71:3 Compliant



Silk Matt	WT153346001	4.95 L	3	36
Matt	WT153646001	4.95 L	3	36
Hardener	WH341045001	0.45 L	1	



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Coatings | Wood

Lacquers

Type

Article number

Packaging

Pcs/transport package

Package/pallet

Bona Traffic Natural

For very busy areas where a natural wood look is desired, with superior protection from the unique Traffic formula. Waterborne, easy to maintain and non-yellowing.



Key Benefits:

- Superior protection for commercial and public areas
- Look and feel of pure wood
- High slip resistance (R9)
- Very low VOC

Technical Data:

Base: Polyurethane
Category: Waterborne 2-comp
Drying time: 3-4 h between coats
Application tools: Bona Roller (AT3100100)
Coverage: 8-10 m²/lit and application

WT190646001

4.5 L

3

36

Bona Mega ONE

Bona Mega ONE focuses on simplifying the craftsman's working day for quicker and easier jobs with great reliability. It brings out a nice, warm wood colouration while establishing a long-lasting protection for wooden floors in domestic and medium wear commercial environments. Clear, non-yellowing formula.



Key Benefits:

- High build characteristics
- Reduced drying time
- Excellent sanding properties
- Non-yellowing

Technical Data:

Base: Polyurethane
Category: Waterborne 2-comp
Drying time: 1-2 h between coats
Application tools: Bona Roller (11 mm)
Coverage: 8-10 m²/L and application

SM	WT300320001	5 L	3	44
Matt	WT300620001	5 L	3	44
Extra Matt	WT300920001	5 L	3	44
SM	WT300313012	1 L	12	50
Matt	WT300613012	1 L	12	50
Extra Matt	WT300913012	1 L	12	50



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Lacquers

Article number

Packaging

Pcs/transport
package

Package/
pallet

Bona Mega

For offices, small shops, hotel rooms and as a premium choice for homes. Innovative, waterborne, one-component formula, that reacts with oxygen and performs like a two-component. No mixing required, use straight from the bottle. Also very good for plank floors and for floors with underfloor heating.

Key Benefits:

- Superior protection for commercial areas
- 1-component with 2-component performance
- Very good for underfloor heating*
- Very low VOC

Technical Data:

Base: Polyurethane

Category: Waterborne 1-comp

Drying time: 2-3 h between coats

Application tools: Bona Roller

Coverage: 8-10 m²/L and application

- Meets DIN 18032:2 for slip resistance (gloss, silk matt & matt)
- EN 71:3 Compliant

*Combined with Bona Prime Intense or Amber



Gloss	WT133013002	1 L	10	50
Gloss	WT133020002	5 L	3	44
Silk Matt	WT133313002	1 L	10	50
Silk Matt	WT133320002	5 L	3	44
Matt	WT133613001	1 L	10	50
Matt	WT133620001	5 L	3	44
Extra Matt	WT133920001	5 L	3	44

Bona Mega Natural

For homes and other spaces where a natural wood look is desired. Waterborne, 1-component formula. Easy to maintain surface.

Key Benefits:

- Superior protection for residential areas
- Look and feel of pure wood
- Very low VOC

Technical Data:

Base: Polyurethane

Category: Waterborne 1-comp

Drying time: 2-3 h between coats

Application tools: Bona Roller (AT3100100)

Coverage: 8-10 m²/lit and application



WT180646001

4.5 L

3

44





Coatings | Wood

Lacquers

Article number

Packaging

Pcs/transport
packagePackage/
pallet

Bona Novia

One-component and waterborne, Bona Novia provides superior protection for floors with normal domestic wear. Can be used with or without primer. Produces an even and warm colour and is non-yellowing. Also very good for cork floors.

Key Benefits:

- Superior protection for domestic areas
- Good resistance to typical household chemicals
- Very low VOC

Technical Data:

Base: Acrylate/polyurethane

Category: Waterborne 1-comp

Drying time: 1–2 h between coats

Application tools: Bona Roller

Coverage: 8–10 m²/L and application
• EN 71:3 Compliant



Gloss	WT230020001	5 L	3	44
Silk Matt	WT230313001	1 L	10	50
Silk Matt	WT230320001	5 L	3	44
Silk Matt	WT230324001	10 L	2	24
Matt	WT230613001	1 L	10	50
Matt	WT230620001	5 L	3	44
Matt	WT230624001	10 L	2	24

Bona Retarder

Bona Retarder is an additive that improves the levelling and prolongs the open time of Bona waterborne finishes, for both primers and topcoats. It is designed to be used when the indoor humidity is low and/or the temperature of the room is higher than normal. Using Bona Retarder will reduce the risk of the finish drying too quickly and leaving roller marks in the dried coat.

Key Benefits:

- Extends open time
- Facilitates application in dry and/or warm climate conditions
- Reduces risk of lap marks



WX100006001

0.2 L

12


120



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®

Want to Become Better?



Bona Education and Training

Be part of a successful team by becoming a Bona Certified Craftsman. As a Bona Certified Craftsman you benefit from the advantages of our strong brand profile and wooden floor expertise.

Becoming a Bona Certified Craftsman assures your customers the highest quality performance and service – giving you better profitability and enabling you to focus on your job – delivering great results.

bona.com/certified

Bona[®]



Coatings | Wood

Sportive System

Type

Article number

Packaging

Pcs/transport
packagePackage/
pallet

Bona Sportive Primer

Primer made especially for handling the flexing and movement of wooden sports floors. Provides excellent adhesion to wood and is easy to apply on large surfaces thanks to excellent levelling properties and long open time. Suitable on practically all types of wood.



Key Benefits:

- No stretched finish or "white lines"
- Excellent abrasion properties
- Extended open time

Technical Data:

Base: Polyurethane
Category: Waterborne 1-comp
Drying time: 2-3 h between coats
Application: Bona Roller
Coverage: 8-10 m²/L and application

WB250024001

10 L

2

24

Bona Sportive Finish

Finish made especially for handling the flexing and movement of wooden sports floors. Excellent levelling properties and long open time make it easy to apply on large surfaces. Approved to both of the leading standards for indoor sports floors (EN 14904:2006 & DIN 18032:2).



Key Benefits:

- High resistance to wear and scuffing
- Perfectly balanced friction
- Easy to maintain

Technical Data:

Base: Polyurethane
Category: Waterborne 2-comp
Drying time: 2-3 h between coats
Application: Bona Roller
Coverage: 8-10 m²/L and application
 • Complies to EN14904:2006 and DIN 18032:2 (suitable friction for sports floors)

Gloss

WT135024001

10.2 L

2

24

Matt

WT136624001

10.2 L

2

24

Bona Masking Tape



Bona Masking Tape is sturdy enough for straight line application and flexible enough to tape circular shapes. The tape stays fixed to the floor and prevents seepage under the tape during paint application.

25 mm width

AX34200000

50 m

72



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Sportive System

Type

Article number

Packaging

Pcs/transport
packagePackage/
pallet

Bona Sportive Paint

Bona Sportive Paint is a specialised line and court marking paint for use on finished wooden sport floors. Can be used to paint linemarkings but also complete court borders and zones. Available in eight mixable vibrant colours to achieve an endless array of shades.

Key Benefits:

- Quick drying
- Requires no abrasion before overcoating
- Superb opacity (hiding ability)

Technical Data:

Base: Polyurethane

Category: Waterborne 1-comp

Drying time: 1–4 between coats

Application: Fine brush or short-haired roller

Coverage: 6–10 m²/lit or 120–200 m of line-marking



	Yellow	WC410155001	1.75 L	2	36
	Red	WC420155001	1.75 L	2	36
	Orange	WC420255001	1.75 L	2	36
	Light Blue	WC430155001	1.75 L	2	36
	Dark Blue	WC430255001	1.75 L	2	36
	Green	WC440155001	1.75 L	2	36
	Black	WC470155001	1.75 L	2	36
	White	WC490155001	1.75 L	2	36

Bona Sportive Cleaner

Concentrated detergent for frequent use on wooden sports floors. Suitable for machine cleaning. Leaves no dulling or slippery residue.

Key Benefits:

- Safe on wood
- Leaves no slippery residue
- Fresh smell

Technical Data:

Dilution: 1:100 for general use



WM640020007	5 L	3	44
-------------	-----	---	----

Bona Sportive Cleaner Plus

Powerful detergent for removing buildup of body fats from sweat and other contaminants that cause the surface to become slippery. Often restores slip resistance and is able to remove black heel marks.

Key Benefits:

- Effective on black heel marks
- Restores in many cases the surface's slip resistance
- Suited for Bona Sportive Finish

Technical Data:

Dilution: 1:5



WM650020006	5 L	3	44
-------------	-----	---	----



ЦИКЛЕВОЧНАЯ
КОМПАНИЯ
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



One promise.
ONE partner.

Introducing Bona Mega ONE.

The one component finish you can depend on for a job well done. Super durable, crystal finish, and great build. It's the new star in the family of Bona wood floor finishes. Mega ONE is clear, it's versatile, and it's Bona. Your best partner for every contracting need.



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Oils – Wear Treatment

Type

Article number

Packaging

Pcs/transport
package

Package/
pallet


Bona Craft Oil

Professional wood oil with excellent saturation properties offering deep protection against wear, chemicals and moisture. Due to its high oil content and outstanding penetration properties only a single application is typically required, making surface treatment a simple and fast job. Equally suitable in homes and public environments. Safe for application on children's toys (EN 71-3). Available in neutral and five coloured versions.

Key Benefits:

- Extremely high degree of saturation for fast surface treatment
- Enhances the grain and colour of the wood
- Low in odour and in solvents (<4%)
- Open, breathing surface

Technical Data:

Base: Modified vegetable oils

Category: Hardening oil, 1-comp

Solids content: 96–98%

Drying time (until use): 24 h

Application: Rubber applicator,

Bona Woolpad or stainless steel trowel

Coverage: 20 m²/L



Pure	GT560115001	2.5 L	4	
Pure	GT560120001	5 L	2	
Pure	GT560113001	1 L	6	
Frost	GT561115001	2.5 L	4	
Frost	GT561113001	1 L	6	
Clay	GT562115001	2.5 L	4	
Clay	GT562113001	1 L	6	
Graphite	GT563115001	2.5 L	4	
Graphite	GT563113001	1 L	6	
Ash	GT564115001	2.5 L	4	
Ash	GT564113001	1 L	6	
Umbra	GT565115001	2.5 L	4	
Umbra	GT565113001	1 L	6	





Coatings | Wood

Oils – Wear Treatment

Type

Article number

Packaging

Pcs/transport
packagePackage/
pallet

Bona Hard Wax Oil

Natural oil, modified for superior protection of wooden floors. Produces the warm look of an oiled floor while establishing a hardwearing and stain resistant surface that is spot-repairable and easy to maintain. Unique composition formulated without questionable substances such as cobalt and ketoximes. Very low in odour and easy to handle, being applicable with roller, brush and trowel. Leaves an open, breathing surface that reduces the risk of side-bonding. Highly suitable for floors with underfloor heating. Combines perfectly with Bona Craft Oil for colouring and changing the design of wooden floors.

Key Benefits:

- Tough and dirt repellent
- Excellent water resistance
- Warm colour and natural look
- Very low in odour
- Free from cobalt and ketoximes (2-butanoxime, butoxime, MEKO)

Technical Data:

Base: Modified vegetable oils & waxes

Category: Hardening oil, 1-comp

Drying time (until use): 24 h

Application tools: Roller, brush or stainless steel trowel

Coverage: 20 m²/L

• EN 71:3 Compliant



Silk Matt	AF3100013	1 L	6	
Silk Matt	AF3100025	2.5 L	2	
Silk Matt	AF3102010	10 L	1	
Matt	AF3600013	1 L	6	
Matt	AF3600025	2.5 L	2	
Matt	AF3602010	10 L	1	
Extra Matt	AF390013001	1 L	6	
Extra Matt	AF390015001	2.5 L	2	
Extra Matt	AF390024001	10 L	1	

Bona Craft Oil 2K

Performance, versatility and design – get the charming look and feel of an oiled floor, plus the protection of a finish. Bona Craft Oil 2K's unique formula, made from modified plantbased oil, exhibits accelerated drying time and strengthened wear resistance. Works perfectly with a wide variety of wood species including otherwise problematic ones such as jabot, cherry, walnut and more. It delivers a beautiful and strong water- and stain-resistant surface and is ready for light use in just 8 hours.

Key Benefits:

- High performance plant-based oil
- Protects in 1 coat
- Long open-time, quick cure
- Overcoatable with Bona Traffic, Bona Traffic HD and Traffic Natural

Technical Data:

Base: Modified vegetable oils incl. isocyanate hardener

Category: Hardening oil, 2-comp

Solids content: 96-98%

Drying time (until use): 12 h

Application tools: Rubber applicator, short-haired roller or stainless steel trowel

Coverage: 20 m²/L



Neutral	GT570014001	1.25 L	6	
Frost	GT571114001	1.25 L	6	
Clay	GT572114001	1.25 L	6	
Graphite	GT573114001	1.25 L	6	
Ash	GT574114001	1.25 L	6	
Umbra	GT575114001	1.25 L	6	
Light Grey	GT576114011	1.25 L	6	
Invisible	GT580014011	1.25 L	6	
Sand	GT579114011	1.25 L	6	



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Oils – Effect Treatment

Type

Article number

Packaging

Pcs/transport
package

Package/
pallet

Bona Mix Colour



Bona Mix Colour is a concentrated pigment paste for waterborne systems and specifically for Bona Nordic Tone and Bona Rich Tone. Added to either of these products it can intensify or change the colour of the Bona Tone to create a special effect.

Technical Data:

Content: Concentrated pigment paste

Consumption: 250 ml for one 5 L bottle (5%) of Bona Nordic Tone or Bona Rich Tone.

Mahogany	GX504007	0.25 L	12	
Walnut	GX504107	0.25 L	12	
White	GX504207	0.25 L	12	
Grey	GX504307	0.25 L	12	
Black	GX504407	0.25 L	12	

Bona Nordic Tone



Bona Nordic Tone is a pre-treatment to Bona Craft Oil for creating the unique character of a Scandinavian white washed floor. Combine with Bona Craft Oil Frost or choose a contrasting colour for an exciting 2-dimensional effect. The colour can be changed or further intensified by adding 5% of Bona Mix Colour to the Tone.

Key Benefits:

- Light, white washed effect
- Inhibits wood yellowing
- Whiteness can be controlled by number of applications (normally only one application is necessary)

Technical Data:

Base: Emulsified oils and waxes, pigmentation

Category: Pre-treatment, 1-comp

Drying time: 1–2 h (between applications)

Application: Oil application sleeve or wide floor brush

Coverage: 8–10 m²/L and application

WX700020001

5 L

3

44

Bona Rich Tone



Bona Rich Tone is a pre-treatment for hardwoods, bringing out a dark, smoky wood colour*, and giving the floor a touch of sophistication. Continue with a layer of Bona Craft Oil in any colour, for an exciting 2-dimensional effect or apply Bona Hard Wax Oil directly for an elegant finish. The colour can be changed or further intensified by adding 5% of Bona Mix Colour.

*the colour is achieved by a chemical reaction to wood and results may vary between wood species. Oak in particular reveals a deep, dark colouration after treatment.

Key Benefits:

- Dark, smoky effect
- Quick drying
- Odourless

Technical Data:

Base: Alkaline solution

Category: Pre-treatment, 1-comp

Drying time: 1–2 h (between applications)

Application: Oil application sleeve

Coverage: 8–10 m²/L and application

WX900020001

5 L

3

44





Coatings | Wood

Oils – Outdoor

Bona Decking Oil








Bona Decking Oil is a concentrated blend of vegetable oils, modified for superior impregnation and the long-lasting protection of decking and other exterior woodwork. It enhances the natural wood grain while protecting against moisture ingress, thus reducing the potential of wood cracking and warping.

Key Benefits:

- Long-lasting protection
- Contains UV protection
- Excellent water repellence

Technical Data:

Base: Modified vegetable oils
Category: Hardening oil, 1-comp
Drying time (until use): 24 h
Application: Wide brush or mohair roller
Coverage: Approx. 20 m²/L

	Neutral	GT551115001	2.5 L	4	
	Neutral	GT551124001	10 L	2	
	Mahogany	GT551215001	2.5 L	4	
	Teak	GT551315001	2.5 L	4	
	Grey	GT551515001	2.5 L	4	

Fillers & Repair

Bona Mix&Fill Plus



Time-saving gap filler with exceptional filling ability (up to 3 mm) often only requiring a single application to achieve a smooth surface. The filler is mixed with wood dust from the actual floor to be treated, producing a natural colouration that blends in with the rest of the floor. Suitable for light to medium coloured wood species.

Key Benefits:

- Exceptional filling ability
- Quick drying
- Anti-corrosive

Technical Data:

Base: Acrylate
Category: Waterborne 1-comp
Drying time (until sanding): 30–60 min
Application: Stainless steel trowel
Coverage: 8–12 m²/L

WF220020001	5 L	3	44
-------------	-----	---	----

Bona Mix&Fill



Gap filler for gaps up to 2 mm wide, suitable for practically all types of wood. The filler is mixed with wood dust from the actual floor to be treated producing a natural colouration that blends in with the rest of the floor.

WF21001302	1 L	10	50
WF21002002	5 L	3	44



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Improved Performance for Resilient Floors



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Coatings | Resilient

Resilient System

Article number

Packaging

Pcs/transport
packagePackage/
pallet

Bona Pure



It serves as a long-term surface protection for heavily trafficked industrial and commercial areas, restoring appearance and simplifying routine maintenance. Bona Pure consists of a waterborne, clear, non-yellowing formula.

Key Benefits:

- Hardwearing PUR protection for resilient floors
- Ultra-quick drying for minimal downtime.
- Optimal application and levelling properties
- Low slip potential and slip resistance compliant to indoor sports surfac

Technical Data:

Category: Waterborne 2-comp
Drying time: 2-4 h between coats
Application tools: Bona Roller (11 mm)
Coverage: 8–10 m²/L and application

	ES205045001	5 L	3	36
Hardener	ES205045001	0.5 L	3	

Bona Pure Colour



Bona Pure Colour ensures a quick application process with accelerated drying properties and being heavily pigmented for coverage in a single coat. Bona Pure Colour is available in eight popular standard colours but can also be ordered in the full spectrum of the RAL and NCS colour palette.

Key Benefits:

- Heavily pigmented for excellent hide
- Ultra-quick drying for minimal downtime
- Available in eight popular standard colours

Technical Data:

Category: Waterborne 2-comp
Drying time: 1-2 h between coats
Application tools: Bona Roller (5 or 11 mm)
Coverage: 8–10 m²/L and application

RAL 5007	EC803620001	5 L	1	
RAL 5014	EC801620001	5 L	1	
RAL 7012	EC802620001	5 L	1	
RAL 6034	EC804620001	5 L	1	
RAL 7038	EC811720001	5 L	1	
RAL 7047	EC812720001	5 L	1	
RAL 1001	EC813720001	5 L	1	
RAL 1015	EC814720001	5 L	1	
Custom	EC800020001	5 L	1	
RAL 5014	EC801613001	1 L	1	
RAL 7012	EC802613001	1 L	1	
RAL 5007	EC803613001	1 L	1	
RAL 6034	EC804613001	1 L	1	
RAL 7038	EC811713001	1 L	1	
RAL 7047	EC812713001	1 L	1	
RAL 1001	EC813713001	1 L	1	
RAL 1015	EC814713001	1 L	1	
Custom	EC800013001	1 L	1	



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Resilient System

Bona LinoPrime



Quick drying PUR-based primer for pore filling of deep cleaned and sanded linoleum floors. Improves levelling and smoothness of the following coat, which typically can be applied already after 1 hour.

Key Benefits:

- Fills pores and reduces absorbency
- Ultra-quick drying
- Essential for linoleum

Technical Data:

Category: Waterborne 2-comp

Drying time: 1-2 h between coats

Application tools: Bona Roller (5 or 11 mm)

Coverage: 8–10 m²/L and application

	EB400620001	5 L	3	36
Hardener	EH390002001	0.2 L	3	

Bona R Creative Chips



Bona Pure Colour ensures a quick application process with accelerated drying properties and being heavily pigmented for coverage in a single coat. Bona Pure Colour is available in eight popular standard colours but can also be ordered in the full spectrum of the RAL and NCS colour palette.

Available in:

- Salt & Pepper
- Black & White
- Terra-mix

Salt & pepper	ES200013501	1 Kg	1	
Black & white	ES200013502	1 Kg	1	
Terramix	ES200013503	1 Kg	1	

Resilient – Maintenance

Bona PowerRemove R



Aggressive cleaning agent developed for stripping polish, dirt and old cleaning residue from resilient floor coverings such as PVC, Linoleum, LVT, or Elastomer. Quick and efficient. Prior to using Bona PowerRemove we recommend to trial whether Bona Remove R can suffice.

Key Benefits:

- For quick removal of old maintenance coatings and contaminants
- Very high degree of efficiency
- Reduced pH prevents alkaline staining

Technical Data:

pH-value: approx. 9 (conc.)

Dilution: 1:1 – 1:5

EM703020001	5 L	3	44
-------------	-----	---	----

Bona Remove R



Detergent based on vegetable oil for frequent cleaning and maintenance of oiled wooden floors. Bona soap nourishes the surface and leaves a thin film that can be buffed for increased shine.

Key Benefits:

- Gentle on oiled surfaces
- Cleans and conditions
- Long lasting concentrate

Technical Data:

pH-value: Approx. 9

Dilution: 1:50

EM702020001	5 L	3	44
-------------	-----	---	----





Floor Care

Proper maintenance is vital when it comes to retaining the long-lasting beauty of wooden floors. Bona's floor care solutions are specially developed for cleaning and revitalising your wooden floors and are made for all finished, oiled and engineered surfaces.

With Bona's unique revitalising solution, Bona Deep Clean System, floor owners can bring back the original lustre of their wood floors instantly, with a unique system that effectively removes the toughest dirt and scuff marks. Read more about Bona Deep Clean System and other best-in-class floor care solutions for both professional users and private homeowners in the following pages.

1. Deep Clean System
2. Lacquer – Maintenance
3. Oils – Maintenance



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Floor Care

Fastening

Sanding

Coatings

Floor Care

Accessories

Deep Clean System

Type

Article number

Packaging

Pcs/transport package

Package/pallet

Bona PowerScrubber



The Bona PowerScrubber is a compact, powerful scrubbing machine for cleaning varnished and oiled wooden floors. When used with Bona Deep Clean Solution, it removes the toughest dirt and grime from wooden floors with ease. The two counter-rotating cylindric brushes clean deeply, even on rough, brushed parquet and wooden floors with bevelled edges. The rubber squeegees ensure an extremely effective water pickup, making it safe to use on wooden floors. Also suitable and recommended for cleaning greyed outdoor deckings.

Key Benefits:

- Powerful and easy to manoeuvre
- Extremely effective water pickup
- Easy to fill, clean and transport
- Indoor and outdoor use

Technical Data:

Motor rating: Max 2700 W, Avg. 1900 W
Power supply: 220–240 V / 50 Hz
Machine weight: 34.5 kg
Scrubbing brush: 2 x 400 mm soft white nylon
Solution capacity: 10 L
Recovery tank capacity: 10 L
Dimensions: 520 mm x 470 mm x 300 mm
Recommended detergents: Bona Deep Clean Solution, Bona Cleaner

AM400201100

1

Roller Brush



White – For oiled or lacquered floors.
 Orange – For profiled deckings.
 Red – For oiled and hard wax oiled floors.
 Green – Lightly abrasive roller for aggressive cleaning of oiled floors.
 Black – Stone and Tiles.

White

AS3647622500

400 mm

1

Orange

AS3647625250

400 mm

1

Red

AS3647624580

400 mm

1

Green

AS3647622520

400 mm

1

Black

AS3647624810

400 mm

1

Suction bar



Replacement suction bar including springs, for the Bona PowerScrubber. Note: Sold per piece, two are needed for a full replacement.

AS3647773230

400 mm

1

Bona Deep Clean Solution



This concentrated cleaner is ideal for thorough, deep cleaning of finished and oiled wooden floors, as well as outdoor decking. Its unique formula delivers optimal cleaning efficiency and removes stubborn scuff marks without the risk of staining the wood. Use it to revitalise dull wooden floors and/or to degrease the surface before applying polish or maintenance oil. Developed for the Bona PowerScrubber, it can, of course, also be used for manual cleaning.

Key Benefits:

- Revitalises dull, dirty floors
- Dissolves deeply engrained dirt and stubborn scuff marks
- Optimised for Bona PowerScrubber

Dilution:

- Dilute with clean water
- Finished surfaces: 1:10
 - Oiled surfaces: 1:20
 - Outdoor deckings: 1:5

WM650020010

5 L

3

44



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Floor Care

Lacquer – Maintenance

Bona Polish Matt



Bona Polish Matt is a waterborne maintenance coating for finished parquet. Reinforced with polyurethane, it leaves an exceptionally durable wear layer, making it suitable for use in both domestic and commercial environments. Offers continued protection against wear without increasing gloss.

Key Benefits:

- Even, matt surface
- Requires no buffing
- High wear resistance

Technical Data:

Base: Acrylate/Polyurethane
Drying time (until use): < 1 h
Application: Bona Microfibre Applicator Pad
Coverage: 50 m²/L

Matt	WP500313001	1 L	10	50
Matt	WP500320001	5 L	3	44

Bona Polish Gloss



Bona Polish Gloss is a waterborne maintenance coating that is compatible with a wide range of surfaces including finished parquet, laminate, linoleum and PVC. Reinforced with polyurethane, it leaves an exceptionally durable wear layer, making it suitable for use in both domestic and commercial environments. Gives the surface new lustre and continued protection against wear.

Key Benefits:

- Good adhesion to many surfaces
- Requires no buffing
- Scuff resistant
- Slip resistance compliant to DIN 18032:2

Technical Data:

Base: Acrylate/Polyurethane
Drying time (until use): < 1 h
Application: Bona Microfibre Applicator Pad
Coverage: 50 m²/L

Gloss	WP511013001	1 L	10	50
Gloss	WP511020001	5 L	3	44

Bona Freshen Up



Bona Freshen Up is a waterborne maintenance coating for the frequent maintenance of finished wooden floors. Based on a pure polyurethane dispersion, it leaves an exceptionally durable wear layer, making it suitable for use in both domestic and commercial environments. Bona Freshen Up is high gloss and gives dull floors new shine and lustre. Meets both EN 14904:2006 and DIN 18032:2 on slip resistance.

Key Benefits:

- Wax-free maintainer
- Allows for future overcoating with waterborne finish
- High wear resistance

Technical Data:

Base: Acrylate/Polyurethane
Drying time (until use): < 1 h
Application: Bona Microfibre Applicator Pad
Coverage: 50 m²/L

WP595013016	1 L	10	50
WP595020002	5 L	3	44



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
 WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Lacquer – Maintenance

Type

Article number

Packaging

Pcs/transport
packagePackage/
pallet

Bona Remover



Bona Remover is a concentrated polish stripper designed to remove Bona Polish and Bona Freshen Up. It can also be used to treat floors which have become slippery and for the removal of black heel marks.

Key Benefits:

- Effective on black heel marks
- Restores in many cases the surface's slip resistance

Dilution:

- Removal of polish: 1 L: 5 L water
- Removal of scuff marks: 1 cap: 100 ml water

WM650013023

1 L

10

50

Bona Cleaner



Concentrated detergent for simple and safe cleaning of finished wood and cork floors. Low foaming and equally suitable for machine cleaning and manual cleaning. Leaves no dulling or slippery residue.

Key Benefits:

- Effective yet safe on wood
- Low foaming
- Fresh smell

Dilution:

- Normal use: 1:100
- Heavily soiled floors: 1:50

WM760013001

1 L

10

50

WM760020001

5 L

3

44





Floor Care

Oils – Maintenance

Article number

Packaging

Pcs/transport
packagePackage/
pallet

Bona Care Oil

Bona Care Oil is a rapid drying maintenance oil for previously oiled wooden floors. The low viscous, unique blend of different vegetable oils, has excellent penetration ability and produces very little odour. Replenishes the pores of the wood for long-lasting protection.

Key Benefits:

- Great coverage rate
- Quick drying
- Low viscosity, easy to spread

Technical Data:

Base: Modified vegetable oils

Category: Hardening oil, 1-comp

Drying time (until use): 12 h

Application: Bona Woolpad or cotton cloth

Coverage: 50–100 m²/L



Pure	GT525113001	1 L	12	60
Pure	GT525120001	5 L	2	50
White	GT525213001	1 L	6	
Grey	GT525313001	1 L	6	

Bona Wax Oil Refresher

Bona Wax Oil Refresher is a maintenance product primarily for Bona Hard Wax Oil. It consists of a concentrate of natural oils and waxes and contains less than 2% solvents. Can also be used on Bona Craft Oil, where increased protection against water and spills is required.

Key Benefits:

- Quick drying
- Low in solvents and odour
- Highly water repellent

Technical Data:

Base: Modified vegetable oils and waxes

Category: Hardening oil, 1-comp

Drying time (until use): 12 h

Application: Bona Woolpad or stainless steel trowel

Coverage: 50–80 m²/L



WP615013001	1 L	12	60
-------------	-----	----	----

Bona Soap

Detergent based on vegetable oil for frequent cleaning and maintenance of oiled wooden floors. Bona soap nourishes the surface and leaves a thin film that can be buffed for increased shine.

Key Benefits:

- Gentle on oiled surfaces
- Cleans and conditions
- Long lasting concentrate

Technical Data:

pH-value: Approx. 9

Dilution: 1:50



WM700013005	1 L	12	45
WM700020001	5 L	3	44



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®

Long-lasting protection



Fast and Effective Decking Revival

For the Outdoor Environment



ЦИКЛЕВОЧНАЯ
КОМПАНИЯ
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Tools & Accessories

Perfect wooden floors can only be achieved with the right tools for the job. Through decades of working closely with craftsmen, Bona has come to understand their every requirement when it comes to working with wooden floors. That is why our tools and accessories are expertly developed for seamless compatibility with all our flooring products. From rollers and gun applicators to dust bags and floor care tools, you will find all the equipment you need for every wood-flooring task in this section.

1. Coatings
2. Fastening
3. Measurement
4. Occupational Safety
5. Floor Care



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Tools & Accessories

Coatings

Type

Article number

Packaging

Pcs/transport package

Package/pallet

Bona Microfiber Roller 11 mm

Microfiber roller for an even application of lacquer producing a low degree of foam. 11 mm pile.



25 cm

AT31002200

1

10

Bona Microfiber Roller 11 mm

Microfiber roller for an even application of lacquer producing a low degree of foam. 11 mm pile.



41,5 cm

AT31002600

1

5

Bona Microfiber Roller 5 mm

Short pile microfiber roller especially suitable for hardwax oil and waterborne paint. 5 mm pile.



25 cm

AT31120897

1

10

Bona Polyester Roller 11 mm

Polyester roller for maintaining an even and high application rate of lacquer. 11 mm pile.



25 cm

AT31002300

1

10

Bona Microfleece Roller 11 mm

Roller with dense microfiber pile for a perfectly smooth application of waterborne finishes. Includes side-guards which help maintain a consistent application rate. 11 mm pile.



25 cm

AT31001000

1

10

WB Roller – Wide

Time-saving roller for application on large surfaces such as sports floors. Functions well with all of Bona's waterborne finishes and primers.



45 cm

AT31451000

1

Velour Roller

Velour roller suited for the application of hardwax oil as well as epoxy.



25 cm

AT31005000

1











**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Tools & Accessories

Coatings	Type	Article number	Packaging	Pcs/transport package	Package/pallet
Edge Roller 	Small sized roller for application to edges. Synthetic fibre.	10 cm	AT31003000	1	
Edge Roller 	Small sized roller with extra large diameter for application of lacquer or paint along edges. 8 mm microfiber pile.	12 cm	AT31002500	1	
Bona Line Roller 	Roller for painting line-markings. Large diameter in order to hold more paint.	55 mm	AT31006000	2	
Roller Handle – 10 cm 	Handle for 10 cm rollers.	10 cm	AT31004000	1	
Roller Handle – 25 cm 	Corrosive resistant handle for 25 cm rollers.	25 cm	AT31014001	1	
Roller Handle – 45 cm 	Aluminium handle with innovative locking function for simple fitting and release of roller. For 45 cm wide rollers.	45 cm	AT31451001	1	
Roller Handle - 30-50 cm 	Adjustable aluminium handle for 30-50 cm wide rollers.	30-50 cm	AT31002800	1	5
Roller Handle – 55 mm 	Handle for 55 mm rollers.	55 mm	AT31006100	1	



ЦИКЛЕВОЧНАЯ
КОМПАНИЯ

Bona®

WWW.PARKET.RU +7 (495) 545-25-85



Tools & Accessories

Coatings

Type

Article number

Packaging

Pcs/transport
package

Package/
pallet

Bona Extension Bar, quick release Professional extension bars in aluminium with quick-release locking function.



110–200 cm

AT31401002

1

Bona Rollerbox

Keeps the roller moist and safe during storage and transportation.



Red / Grey

AT31405000

1

Floor Brush

High-quality floor brush with tightly packed, fine bristles. Suitable for hard wax oil and decking oil.



22 cm

AT31101000

1

Floor Brush

Floor brush for application of oil and lye, fits on extension bar.



20 cm

AT953203

1

Floor Brush Pro

Durable floor brush with tightly packed fine bristles made specifically for applying waterborne finish, waterborne paint and lye. Supplied in a convenient cover for safe storage and transportation.



30 cm

AT953214

1

Applicator Handle

Swivel head applicator handle for Oil Application Sleeve.



45 cm

AT954225

1

Oil Application Sleeve

Sleeve made of synthetic fibre for application of low viscosity oil. Also suitable for Bona Nordic Tone and Bona Rich Tone.



45 cm

AT954224

1











**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Tools & Accessories

Coatings	Type	Article number	Packaging	Pcs/transport package	Package/pallet
Applicator Handle 	Swivel-head applicator handle for Applicator Sleeve.				
	46 cm	AT956904	1		
Applicator Sleeve 	Foam and synthetic fibre sleeve for applying waterborne finish.				
	46 cm	AT956903	1		
Oil Squeegee 	Oil-resistant squeegee for quick and simple application of Bona Oils. Can be attached to extension bar.				
	50 cm	AT31302001	1		
Disposable Booties 	Single-use plastic shoe covers.				
		AT33051000	50		
Stainless Steel Trowel 	Stainless steel trowel for waterborne finishes, oils and fillers.				
	27 cm	AT959201	1		
	35 cm	AT31360350	1		
Scraper 	A floor scraper for those hard-to-reach areas such as corners, and close to the skirting board.				
	4 cm	AT929502	1		
U-blade 	4 cm	AT929503	1		
	2 cm	AT929504	1		
Cotton Cloth 	Rip-resistant cotton cloths for oiling, cleaning and buffing jobs.				
	50 x 55 cm	AT32086000	10 pcs		





**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Tools & Accessories

Coatings	Type	Article number	Packaging	Pcs/transport package	Package/pallet
	Lamella, Oak	Oak lamellas for repairing parquet floors.			
		337 x 68 x 4 mm	P901201	44 pcs	
	Bona Mixing Bottle	Mixing bottle with clear volume markings that simplify the decantation of two-component finishes. Includes markings for Bona Traffic HD, Traffic, Traffic Anti Slip, Natural 2-comp & Bona Wave.			
		max. 1.9 L	30031	72 pcs	



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona around the world

Assembly London

A rooftop bar with a beautiful, highly durable floor.

Assembly London is an urban hotel in London's West End. The rooftop bar features a 20 mm engineered, dark fumed oak parquet floor, which had to be fitted quickly and provide optimal durability to stand up to the traffic of a busy metropolitan bar.

The floor was installed and finished by a Bona Certified Contractor using Bona D501 primer applied to the WBP plywood subfloor. Wire brushed parquet blocks were glued using Bona R848 silane adhesive, then finished with Bona Craft Oil 2K (Frost) and buffed to create a whitewashed effect and reduce the darkness of the fumed oak. To retain the beauty and provide optimal protection, two coats of Bona Traffic HD (silk matt) lacquer were applied delivering a speedy but beautiful result.

Bona

Fastening

Sanding

Coatings

Floor Care

Accessories



Tools & Accessories

Coatings

Type

Article number

Packaging

Pcs/transport package

Package/pallet

Bona Wax Repair Kit



Complete set for making quick and easy repairs to damaged wood, cork or laminate surfaces. The set includes 20 durable hardwax sticks and a butane-driven hot knife to melt the wax. The many different colours in the set will suit most wood types as is but it is also possible to combine waxes for a perfect match. The melted wax doesn't slump, making it possible to fill significant damages in the surface. Once set, the wax forms a hard, wear-resistant surface.

Key Benefits:

- Suitable for all types and colours of wood
- Capable of filling large scratches and cavities in the surface
- Fast repairs, repair is done and ready in a few minutes

Contents:

- Butane-driven hot knife
- 20 hard wax sticks
- Scraper
- Wiping cloth
- Needle

AT32053600

1

Wax Repair Stick

01 Transparent

AT32053001

1

02 Pine

AT32053002

1

Dark oak

AT32053003

1

04 Beech

AT32053004

1

05 Pear

AT32053005

1

06 Oak

AT32053006

1

07 Cherry

AT32053007

1

08 Birch

AT32053008

1

09 Light oak

AT32053009

1

10 Ash

AT32053010

1

11 Brown

AT32053011

1

12 Yellow

AT32053012

1

13 Eggshell

AT32053013

1

14 Grey

AT32053014

1

16 Cream

AT32053016

1

17 Red

AT32053017

1

19 Green

AT32053019

1

20 Blue

AT32053020

1

21 White

AT32053021

1

22 Black

AT32053022

1

Hot Knife



Butane-driven hot knife for melting wax when repairing damages in wooden floors. Reaches operating temperature directly.

AT32053100

1



ЦИКЛЕВОЧНАЯ
КОМПАНИЯ

Bona

WWW.PARKET.RU +7 (495) 545-25-85



Tools & Accessories

Fastening

Sanding

Coatings

Floor Care

Accessories

Fastening

Type

Article number

Packaging

Pcs/transport
packagePackage/
pallet

Notched Blade Handle

For application of levelling compounds. Height adjustable.



560 mm

AT31444000

1

Notched Blade R2 560 mm

Application of levelling compounds.



3 mm

AT31444001

10

5 mm

AT31344402

10

Plastic Bucket

30-litre mixing bucket.



30 L

AT31408000

1

Stir Stick

Stir stick for mixing two-component adhesives or primers.



80 mm

AT32051080

1

Pull Bar

Pulling iron for installation of parquet. 55 cm long.



AT32033000

1

Tapping block

Tapping block made of polyamide for bonded installation. Without handle.



AT32038000

1

Spike Roller

For venting levelling compounds. 50 cm wide.



50 cm

AT32052500

1

Spike Shoes

Nail shoes to be able to walk around in freshly applied material such as levelling compounds or epoxy primers.



AT32055000

1 pair



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Tools & Accessories

Fastening

Bona Cleaning Wipes



Cleaning wipes for hard-to-remove materials. The textured tissue surface enables deep cleaning and easy dirt removal.

AT322100

72

Cork Strips



Cork strips for filling gaps between e.g. tile and wood flooring.

900 x 8 x 10 mm

AX34001000

25

900 x 8 x 10 mm

AX34002000

25

900 x 8 x 10 mm

AX34003000

25

900 x 8 x 10 mm

AX34004000

25

900 x 8 x 10 mm

AX34006000

30

Liquid Cork



Liquid cork for filling gaps.

AX34009000

30

Measurement

Calcium Carbide Ampoules

Calcium carbide ampoules for CM Device.



AT37001020

20 pcs

20

AT37001100

100 pcs

100

GANN CM Device



Complete CM kit for professional moisture measurement. Includes all tools necessary to make a standardised measurement.

AT37001200

1



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Tools & Accessories

Measurement

Article number

Packaging

Pcs/transport
package

Package/
pallet

GANN Hydromette RTU 600

Quadruple measurement instrument for wood, subfloors, air humidity and temperature, incl. electrode RF-T28.



AT37004000

1

GANN Hydromette Compact B

Non-destructive moisture measurement for screeds.



AT37008000

1

Surface Hardness Tester

Surface hardness tester for screeds including guide plate.



AT37010000

1

V-Head

For evaluating surface evenness.



AT37012000

1

Fastening

Sanding

Coatings

Floor Care

Accessories



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Tools & Accessories

Occupational Safety

	Article number	Packaging	Pcs/transport package	Package/pallet
3M Respirator Mask, 9310  Dust mask P1 against compact particles.	AT33011100		20	
3M Respirator Mask, 9322  Dust mask P2 against respirable dust.	AT33012100		10	
3M Respirator Mask, 9332  Dust mask P3 against respirable dust, with exhalation valve. Can be cleaned, therefore reusable.	AT33013100		10	



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Tools & Accessories

Fastening

Sanding

Coatings

Floor Care

Accessories

Floor Care

Type	Article number	Packaging	Pcs/transport package	Package/pallet
------	----------------	-----------	-----------------------	----------------

Polish Applicator



Polish applicator including a fine cotton sleeve. Suitable for Bona Freshen Up and Bona Polish.

40 cm	AT31409000		1	
-------	------------	--	---	--

Extra Cotton Sleeve

Waxing tool for applying Bona Freshen Up and Bona Polish.

40 cm	AT31409001		1	
-------	------------	--	---	--

Commercial System Kit



Lightweight yet sturdy telescopic pole made of brushed aluminium for superior durability. The 60 cm wide mop base is specially designed with a raised edge that helps trap dirt and increases scrubbing pressure. Delivered with 1 Dusting Pad and 1 Cleaning Pad.

60 cm	WM710013489	1	10	
-------	-------------	---	----	--

Dusting Pad



Pad, designed to be used dry. Consisting of a special mix of short and long fibres with an electrostatic charge to trap and remove loose dust, dirt and debris, quickly and safely from floors.

60 cm	AX0003543	1	12	
-------	-----------	---	----	--

Cleaning Pad



Pad, designed to be used wet. Consisting of highly absorbent microfiber with a lot of scrubbing action for removing bonded dirt.

60 cm	AX0003544	1	12	
-------	-----------	---	----	--



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®



Application Advice

1. Lacquer System
2. Natural Wood Look
3. Sportive System
4. Craft Oil 2K System
5. Oil System
6. Hard Wax Oil



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®

- 1.** Sanding – Coarse and medium with Belt and Edge Sander or the Bona Power Drive




- 2.** Application – Bona Mix&Fill Plus with a trowel

Consumption: 8–12 m²/lt
Drying time: 15–30 min.
(20 °C, 60%)



- 3.** Sanding – Fine with Belt and Edge Sander



- 4.** Sanding – Final with Bona FlexiSand



- 5.** 1st application – Choose one of the below Bona base coats and apply with Bona Microfiber Roller



Bona White
White washed look
1-3x with roller



Bona Natural
Look of pure wood
1-2x with roller



Bona Classic
The all-rounder
1-3x with roller



Bona Intense
Medium colouration
1x with roller



Bona Amber
Rich colouration
2x with roller



Bona Quick
Quick drying gel
3x with trowel



- 6.** 2nd application – Choose one of the below Bona topcoats and apply with Bona Microfiber Roller



Domestic wear



Bona Nova
Consumption:
8–10 m²/lt
Drying time: 1–2 h
(20 °C, 60%)

Heavy wear



Bona Mega
Consumption:
8–10 m²/lt
Drying time: 2–3 h
(20 °C, 60%)

or



Bona Mega ONE
Consumption:
8–10 m²/lt
Drying time: 1–2 h
(20 °C, 60%)

Very heavy wear



Bona Traffic HD
Consumption:
8–10 m²/lt
Drying time: 2–3 h
(20 °C, 60%)

or



Bona Traffic
Consumption:
8–10 m²/lt
Drying time: 3–4 h
(20 °C, 60%)

- 7.** Intermediate sanding with Bona FlexiSand or Bona Buffer



- 8.** 3rd application – with the same Bona topcoat as used before



- 9.** If extreme traffic is expected, an additional application of top coat is recommended



Natural Wood Look

1. Sanding – Coarse and medium with Belt and Edge Sander or the Bona Power Drive
2. Application – Bona Mix&Fill Plus with a trowel
3. Sanding – Fine with Belt and Edge Sander
4. Sanding – Final with Bona FlexiSand
5. 1st application – Bona Natural with Bona Microfiber Roller



Consumption: 8–12 m²/lt
Drying time: 15–30 min
(20 °C, 60%)



Domestic wear



Bona Natural
Consumption:
8–10 m²/lt
Drying time: 1–2 h
(20 °C, 60%)

Very heavy wear



Bona Natural
Consumption:
8–10 m²/lt
Drying time: 1–2 h
(20 °C, 60%)

6. 2nd application – Bona Mega Natural with Bona Microfiber Roller



Mega Natural
Consumption:
8–10 m²/lt
Drying time: 2–3 h
(20 °C, 60%)

- 2nd application – Traffic Natural with Bona Microfiber Roller



Traffic Natural
Consumption:
8–10 m²/lt
Drying time: 3 h
(20 °C, 60%)

Mix Natural 2-comp. with
hardener – shake for 2 mins

7. Intermediate sanding with Bona FlexiSand or Bona Buffer



- Intermediate sanding with Bona FlexiSand or Bona Buffer



8. 3rd application – Bona Mega Natural

- 3rd application – Traffic Natural



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®

Sportive System

1. Sanding – Coarse and medium with Belt and Edge Sander or the Bona Power Drive



2. Application – Bona Mix&Fill Plus with a trowel

Consumption: 8–12 m²/lt
Drying time: 15–30 mins
(20 °C, 60%)



3. Sanding – Fine with Belt and Edge Sander



4. Sanding – Final with Bona FlexiSand or Bona Buffer

5. 1st Application – Bona Sportive Primer with the Bona Microfiber Roller

Sportive Primer
Consumption: 8–10 m²/lt
Drying time: 2–3 h
(20 °C, 60%)



6. 2nd Application – Bona Sportive Finish with the Bona Microfiber Roller

Sportive Finish
Consumption: 8–10 m²/lt
Drying time: 2–3 h
(20 °C, 60%)

Mix Sportive Finish with
Sportive Hardener –
shake for 1 min



7. Intermediate sanding with Bona FlexiSand or Bona Buffer



8. Application – Line marker with Bona Sportive Paint



Sportive Paint
1 litre for approx. 80 m x 5 cm lines
1 litre for approx. 100 m x 4 cm lines

9. Intermediate sanding with Bona FlexiSand or Bona Buffer and Bona Scrad System



10. 3rd and 4th application with Bona Sportive Finish with Bona Microfiber Roller



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®

Craft Oil 2K System

1. Sanding – Coarse and medium with Belt and Edge Sander or the Bona Power Drive



2. Application – Bona Mix&Fill Plus with a trowel

Consumption: 8–12 m²/lt
Drying time: 15–30 min
(20 °C, 60%)



3. Sanding – Fine with Belt and Edge Sander



4. Sanding – Final with Bona FlexiSand or Bona Buffer



5. Application – Bona Craft Oil 2K

Consumption: approx. 30 m²



6. Remove surplus with cotton cloths



7. Application – Bona Traffic HD, Bona Traffic or Traffic Natural after min 8 h (12 h for pigmented oil)

Consumption: 8–10 m²/lt
Drying time: 3–4 h
(20 °C, 60%)



8. Intermediate sanding with Scrad Pad



9. 2nd application – Using the same product as in the previous layer



Bona Traffic HD
Consumption:
8–10 m²/lt
Drying time: 2–3 h
(20 °C, 60%)

or



Bona Traffic
Consumption:
8–10 m²/lt
Drying time: 3–4 h
(20 °C, 60%)



Traffic Natural
Consumption:
8–10 m²/lt
Drying time: 3 h
(20 °C, 60%)


10. If extreme traffic is expected, an additional application of topcoat is recommended



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®

1. Sanding – Coarse and medium with Belt and Edge Sander or the Bona Power Drive




2. Application – Bona Mix&Fill Plus with a trowel

Consumption: 8–12 m²/lt
Drying time: 15–30 min
(20 °C, 60%)



3. Sanding – Fine with Belt and Edge Sander



4. Sanding – Final with Bona FlexiSand or Bona Buffer



5. Application of Bona Oil System – Choose one of the 3 treatments

Pure Oil treatment

Apply Bona Craft Oil with rubber blade, steel trowel or Bona Wool Pad until wood is saturated



Massage oil into wood using green pad for neutral oil, or red pad for coloured oil, attached to Bona FlexiSand



Remove surplus oil with cotton cloth and allow to dry




For best results dry buff surface with Bona Wool Pad.



Oil treatment with Bona Nordic Tone

Apply Bona Nordic Tone with an application sleeve. Leave to dry for 4–5 hours



Fine sanding using Bona FlexiSand and Bona Scrad Pad. Remove dust with a vacuum cleaner



Apply Bona Craft Oil with rubber blade, steel trowel or Bona Wool Pad until wood is saturated



Massage oil into wood with red pad attached to Bona FlexiSand

Remove surplus oil with cotton cloth and allow to dry




For best results dry buff surface with Bona Wool Pad.



Oil treatment with Bona Rich Tone

Apply Bona Rich Tone with an application sleeve. Leave to dry for 4–5 hours



Fine sanding using Bona FlexiSand and Bona Scrad Pad. Remove dust with a vacuum cleaner



Apply Bona Craft Oil with rubber blade, steel trowel or Bona Wool Pad until wood is saturated



Massage oil into wood with red pad attached to Bona FlexiSand

Remove surplus oil with cotton cloth and allow to dry



For best results dry buff surface with Bona Wool Pad.



Apply a thin coat of Bona Hard Wax Oil. Allow 8–10 hours for drying





Pure Titan Strength

Bona Titan – The next generation of powerful adhesives



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®

Hard Wax Oil

1. Sanding – Coarse and medium with Belt and Edge Sander or the Bona Power Drive



2. Application – Bona Mix&Fill Plus with a trowel

Consumption: 8–12 m²/lt
Drying time: 15–30 min
(20 °C, 60%)



3. Sanding – Fine with Belt and Edge Sander



4. Sanding – Final with Bona FlexiSand or Bona Buffer



5. Matt/Silk Matt

- 5.1 1st application with Bona Hard Wax Oil.
Apply a thin layer with a Velour Roller

Application tool: Bona Velour Roller



Bona Hard Wax Oil
Consumption: Depending on
type of wood – approx. 1 L
for 20–24 m².
Drying time: 6–8 h



- 5.2 Abrade with Bona Scrad Pad



- 5.3 2nd application: Very thin layer
with a Velour Roller



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®

Flooring	EN/DIN Standard	Type	Consumption g/m ²	R777/R778	R848	R848T	R850/R850T	Titan	D705	D720
Parquet strip and mosaic parquet finger 1-layer (solid) unfinished elements	EN 13226	parquet strip of oak and similar wood types	1000/1250	✓	—	✓	✓	✓	✓	✓
	EN 13226	parquet strip of beech and similar highly-absorbent wood types	1000/1250	✓	—	✓	✓	✓	✓	✓
	EN 13488	mosaic parquet finger	850	✓	✓	✓	✓	✓	✓	✓
	EN 13228	blocks/overlay, oak or similar wood width/thickness < 5/1	1000/1250	✓	—	✓	✓	✓	✓	✓
	EN 13228	blocks/overlay, beech and similar highly-absorbent wood types < 5/1	1000/1250	✓	—	—	✓	✓	✓	✓
	EN 14761	wood flooring - solid wood parquet – vertical finger, wide finger and module brick – 10/16/22 mm	1000/1250	✓	✓*	✓*	✓*	✓	✓	✓
	EN 13227	wood flooring – solid lam parquet products up to 25 x 5 cm, oak and similar wood types	1000	✓	—	—	✓	✓	✓	✓
	EN 13227	wood flooring – solid lam parquet products up to 25 x 5 cm, beech and similar highly-absorbent wood types	1000	✓	—	—	✓	✓	✓	✓
	EN 13629	solid hardwood flooring and solid hardwood flooring composite elements	1000	✓	—	—	✓	✓	—	—
	EN 13629	wood flooring – solid lam parquet products larger than 25 x 5 cm	1250/1500	✓	—	—	—	✓	—	—
1-layer parquet element, factory prefinished	EN 13488	small formats, oak and similar wood types	850	✓	✓	✓	✓	✓	✓	✓
	EN 13488	small formats, beech and similar highly-absorbent wood types	850	✓	—	—	✓	✓	✓	✓
	EN 13226	parquet strip with groove and tongue	1000/1250	✓	—	✓	✓	✓	✓	✓
Multilayered parquet element, factory prefinished	EN 13489	2-layer, parquet strip	1000	✓	✓	✓	✓	✓	✓	✓
	EN 13489	2-layer, parquet panel	1000/1250	✓	✓	✓	✓	✓	—	—
	EN 13489	3-layer flooring board: < 13 mm thick	1250	✓	✓	✓	✓	✓	✓	✓
	EN 13489	3-layer flooring board: 10–13 mm thick, less than 1200 mm	1250	✓	✓	✓	✓	✓	✓	✓
	EN 13489	3-layer flooring board: 10–13 mm thick, longer than 1200 mm	1250	✓	✓	✓	✓	✓	—	—
Multilayered parquet element, unfinished	EN 13489	2-layer	1000	✓	✓	✓	✓	✓	✓	✓
Wood block (end grain floors)	DIN 68702	Wood block RE & WE up to 40 mm thickness	1000/1500	—	—	—	—	✓	✓	✓
	DIN 68702	Wood block GE > 40 mm thickness (industrial)	1250/1500	—	—	—	—	—	—	—

* R848/R848T/R850/R850T only for 16 and 22 mm

Subfloor Construction	Binding Material according to EN 13813	Type of subfloor	R777/R778	R848	R848T	R850/R850T	Titan	D705	D720
Floating screed including calcium sulphate screed also with underfloor heating system and self-levelling compounds	CT	Cementitious (heated) screed	✓	✓	✓	✓	✓	✓	✓
	CA	Calcium sulphate (heated) screed	✓	✓	✓	✓	✓	—	—
	CA	Calcium sulphate floating screed	✓	✓	✓	✓	✓	—	—
	AS	Mastic asphalt, well-sanded**	✓	✓	✓	✓	✓	—	—
	CT/CA	Self-levelling compounds	✓	✓	✓	✓	✓	✓	✓
Wooden substrate		Chipboard, OSB, plywood	✓		✓	✓	✓	✓	✓

General: Whether you use a fine or coarse trowel depends on the condition of the subfloor and the dimensions of the parquet elements

****** When using Bona's silane-based adhesives, a protection primer such as R540 or Bona R410 is necessary prior to the installation of the parquet

Bona R848: can be used under suitable conditions for the installation of solid parquet, such as mosaic and block parquet with proper dimensions. Please contact your local Bona technical team for more information.

Index of Bona Adhesives

Overview of the technical properties of our reactive primers and adhesives

Product name	Base	Consumption of primer in g/m ²	Consumption as moisture barrier on CT or concrete floors in g/m ²	Barrier effect up to max. residual moisture content	Drying time in general/ Drying time in combination with our reactive adhesives
R410*	2-comp. epoxy resin	Approx. 150–250	Approx. 500 (two applications)	Yes, up to max. 5.0 cm/%	224 h with Bona R777/R778 and Bona silane based adhesives
R540	1-comp. polyurethane	Approx. 150–250	Approx. 300 (two applications)	Yes, up to max. 4.0 cm/%	1 h with Bona R777/R778 24 h with all Bona silane based adhesives
R590*	Silane based	500	500 (with one application)	Yes, up to max. 5.0 cm/% or 90% relative air humidity	4-6 h with all Bona silane based adhesives

* The broadcasting of quartsand (grit size 0.3–0.8) is possible prior to the usage of a Bona levelling compound.

Special note:

- Bona R410 can be diluted with 20% of Bona S100 in order to achieve a deeper penetration of the primer.
- Normally, concrete floors need to be shot-blasted as a mechanical pre-treatment.
- For any further processing information, please view our technical data sheets at www.bona.com

Please note: Our suggestions and recommendations are carefully provided based on our general terms and conditions. Installation and working parameters are followed to the best of our knowledge, give no entitlement of completeness and do not disabuse for the final checkup of the proposals and products on its applicability at the designated range of use (i.e. by making sample areas according to DIN 18356.) The observance of notes of the packaging, labels, technical data sheets, operating, handling and processing instructions as well as marks and appropriate technical guidelines and norms and the accomplishment of the job through a commercial contractor is presupposed according to the adequate instructions.



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®

Index - Products

Product	Page	Product	Page
3M Respirator Mask, 9310	78	Bona masking tape	52
3M Respirator Mask, 9322	78	Bona Mega	49
3M Respirator Mask, 9332	78	Bona Mega Natural	49
Adapter kit 1	17	Bona Mega ONE	48
Adapter kit 2	17	Bona Microfiber Roller 11 mm	69
Applicator Handle	71	Bona Microfiber Roller 5 mm	69
Applicator Handle	72	Bona Microfleece Roller 11 mm	69
Applicator Sleeve	72	Bona Mini Buffer	30
Bona 8100 Double-sided Disc	38	Bona Mix Colour	57
Bona 8100 Silicon Carbide Disc	37	Bona Mix&Fill	58
Bona 8100 Silicon Carbide Roll	38	Bona Mix&Fill Plus	58
Bona 8300 Antistatic Belt	33	Bona Mixing Bottle	73
Bona 8300 Antistatic Disc	35	Bona Multidisc	25
Bona 8300 Antistatic Roll	34	Bona Natural	45
Bona 8300 Antistatic Sleeve	33	Bona Net Alox	43
Bona 8500 Aluminium Oxide Belt	36	Bona Net Ceramic	43
Bona 8500 Aluminium Oxide Sleeve	36	Bona Nordic Tone	57
Bona 8700 Belt	32	Bona Notched Trowel	15
Bona 8700 Ceramic Disc	32	Bona Novia	50
Bona 8700 Roll	32	Bona OptiSpread	13
Bona Amber	46	Bona Pad 200 mm	40
Bona Belt	20	Bona Pad 407 mm	39
Bona Belt HD	19	Bona Pad Drive	25
Bona Belt Lite	20	Bona Polish Gloss	64
Bona Buffer	28	Bona Polish Matt	64
Bona Care Oil	66	Bona Polyester Roller 11 mm	69
Bona CEE Adapter	19	Bona Power Drive	25
Bona Classic	45	Bona Power Drive NEB	26
Bona Cleaner	65	Bona PowerRemove R	61
Bona Cleaning Pad	42	Bona PowerScrubber	63
Bona Cleaning Wipes	76	Bona Pure	60
Bona CombiEdge	23	Bona Pure Colour	60
Bona CombiEdge Stair Support	23	Bona Quattro Disc	25
Bona Concrete Disc	28	Bona Quick	46
Bona Craft Oil	55	Bona R200	10
Bona Craft Oil 2K	56	Bona R400	3
Bona D500	5	Bona R405	3
Bona D501	5	Bona R410	4
Bona D510	5	Bona R440	3
Bona D700	9	Bona R540	4
Bona D705	9	Bona R580 Trowel	15
Bona D720	10	Bona R590	4
Bona D750	10	Bona R770	10
Bona DCS 25	18	Bona R777	11
Bona DCS 70	17	Bona R778	11
Bona Decking Oil	58	Bona R848	11
Bona Decor Paint	46	Bona R848T	12
Bona Deep Clean Solution	63	Bona R850	12
Bona Diamond Abrasive Disc	42	Bona R850T	12
Bona DualEdge	24	Bona R880	13
Bona Edge	22	Bona R Creative Chips	61
Bona Edge XL	22	Bona Remover	65
Bona Expansion Strips	8	Bona Remove R	61
Bona Extension Bar, quick release	71	Bona RenoForce	13
Bona Fibres	8	Bona Retarder	50
Bona FlexiSand	24	Bona Rich Tone	57
Bona FlexiVaccum	27	Bona Rollerbox	71
Bona Freshen Up	64	Bona S100	5
Bona Gap Master	14	Bona S20	30
Bona H600	7	Bona Sanding Screen, double-sided	41
Bona H605	7	Bona Scorpion	21
Bona H610	7	Bona Scorpion DCS	21
Bona H660 Object	7	Bona Scrad Pad	40
Bona H670 Gypsum	8	Bona Scrad Wing	40
Bona Hard Wax Oil	56	Bona Soap	66
Bona Intense	45	Bona Sportive Cleaner	53
Bona Intermediate Pad	42	Bona Sportive Cleaner Plus	53
Bona Line Roller	70	Bona Sportive Finish	52
Bona LinoPrime	61	Bona Sportive Paint	53



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85



Index - Products

Product	Page	Product	Page
Bona Sportive Primer	52	Oil Squeegee	72
Bona Superpad 280 mm	39	PCD Maxi Segment	28
Bona Superpad 407 mm	39	Plastic Bucket	75
Bona Superpad Incl. EAN code	39	Polish Applicator	79
Bona Supraflex	27	Power Stripper	31
Bona Titan	13	Pull Bar	75
Bona Traffic	47	Quartz Sand	15
Bona Traffic Hardener	47	Quattro disc	25
Bona Traffic HD	47	Replacement Pad Set	25
Bona Traffic HD Anti Slip	47	Roller Brush	63
Bona Traffic HD Hardener	47	Roller Handle – 10 cm	70
Bona Traffic Natural	48	Roller Handle – 25 cm	70
Bona U300	8	Roller Handle – 45 cm	70
Bona U310	9	Roller Handle – 30-50 cm	70
Bona U340	9	Roller Handle – 55 mm	70
Bona Wax Oil Refresher	66	Safety belt	19
Bona Wax Repair Kit	74	Sanding disc	29
Bona White	45	Scraper	72
Bona Wool Pad	40	Spike Roller	75
Calcium Carbide Ampoules	76	Spike Shoes	75
Cartridge Applicator	15	Split segment	28
Cleaning Pad	42	Stainless Steel Trowel	72
Commercial System Kit	79	Stir Stick	75
Cork Strips	76	Suction bar	63
Cotton Cloth	72	Surface Hardness Tester	77
Cup Brush Metal M14	27	Tapping block	75
Cup Brush Nylon M14	27	Transport cart	19
Delta Abrasive Paper	42	Transport cart	20
Diamond Segment	28	Tynex Distressing Drum	22
Disposable Booties	72	U-blade	72
Drive Disc	29	V-Head	77
Drive Disc	30	Vacuum unit ASO5	29
Dust Bag – Cloth	29	Vacuum Sealing Ring	29
Dust Bag – Flexivacuum	27	Velour Roller	69
Dust Bag – Paper	29	Wave bonders	3
Dust Bags LongoPac	17	WB Roller – Wide	69
Dusting Pad	79	Wax Repair Stick	74
Edge Roller	70		
External Soft Start	20		
Extra Cotton Sleeve	79		
Extra Weight	20		
Extra Weight	24		
Extra Weight	28		
Fein MultiMaster saw blades	31		
Fein MultiMaster Start MSX636	31		
Fleece Dust Bag	18		
Flex Filter Dust Bag	27		
Floor Brush	67		
Floor Brush	71		
Floor Brush Pro	71		
GANN CM Device	76		
GANN Hydromette Compact B	77		
GANN Hydromette RTU 600	77		
Hitachi CV 300	30		
Hot Knife	74		
Internal Spur Gear	26		
Lamella, Oak	73		
LED lamp	25		
Liquid Cork	76		
Metal Distressing Drum	22		
Microfiber Dust Bag Large	21		
Microfiber Dust Bag Small	24		
Microfiber Pad	40		
NEB Metal Brush	26		
NEB Sanding Disc	26		
NEB Tynex Brush	26		
Notched Blade Handle	75		
Notched Blade R2 560 mm	75		
Oil Application Sleeve	71		



**ЦИКЛЕВОЧНАЯ
КОМПАНИЯ**
WWW.1PARKET.RU +7 (495) 545-25-85

Bona®

Index - Article Numbers

Article No.	Page	Article No.	Page	Article No.	Page	Article No.	Page
30031	70	AAS466800363	38	AAS467700803	33	AAS469600363	32
AA68001000	39	AAS466800403	38	AAS467701003	33	AAS469600503	32
AA68002000	39	AAS466800603	38	AAS467701203	33	AAS470600245	35
AA68003000	39	AAS466800803	38	AAS467701503	33	AAS470600365	35
AA68004000	39	AAS466801003	38	AAS467800243	33	AAS470600406	35
AA68041000	39	AAS466801203	38	AAS467800363	33	AAS470600606	35
AA68042000	39	AAS466900165	37	AAS467800403	33	AAS470600806	35
AA68043000	39	AAS466900245	37	AAS467800603	33	AAS470601006	35
AA68052000	40	AAS466900365	37	AAS467800803	33	AAS470601206	35
AA68053000	40	AAS466900406	37	AAS467801003	33	AAS470700361	32
AA68054000	40	AAS466900506	37	AAS467801203	33	AAS470700501	32
AA68055000	40	AAS466900606	37	AAS467900163	36	AAS470800361	32
AA68071000	40	AAS466900806	37	AAS467900243	36	AAS470800501	32
AA970740	40	AAS466901006	37	AAS467900363	36	AAS470900361	32
AAS466000161	38	AAS466901206	37	AAS467900403	36	AAS470900501	32
AAS466000241	38	AAS466901506	37	AAS467900503	36	AAS471100245	35
AAS466000361	38	AAS467100165	37	AAS467900603	36	AAS471100365	35
AAS466000401	38	AAS467100245	37	AAS467900803	36	AAS471100406	35
AAS466000501	38	AAS467100365	37	AAS467901003	36	AAS471100606	35
AAS466000601	38	AAS467100406	37	AAS467901203	36	AAS471100806	35
AAS466000801	38	AAS467100506	37	AAS468000163	36	AAS471101006	35
AAS466001001	38	AAS467100606	37	AAS468000243	36	AAS471101206	35
AAS466001201	38	AAS467100806	37	AAS468000363	36	AAS471200606	35
AAS466300241	34	AAS467101006	37	AAS468000403	36	AAS471200806	35
AAS466300361	34	AAS467101206	37	AAS468000503	36	AAS471201006	35
AAS466300401	34	AAS467400245	35	AAS468000603	36	AAS471201206	35
AAS466300601	34	AAS467400365	35	AAS468000803	36	AAS471600365	32
AAS466300801	34	AAS467400406	35	AAS468001003	36	AAS471600505	32
AAS466301001	34	AAS467400606	35	AAS468001203	36	AAS471700365	32
AAS466301201	34	AAS467400806	35	AAS468200163	36	AAS471700505	32
AAS466400241	34	AAS467401006	35	AAS468200243	36	AAS471800365	32
AAS466400361	34	AAS467401206	35	AAS468200363	36	AAS471800505	32
AAS466400401	34	AAS467500245	35	AAS468200403	36	AAS471902408	42
AAS466400601	34	AAS467500365	35	AAS468200503	36	AAS472000808	42
AAS466400801	34	AAS467500406	35	AAS468200603	36	AAS472001208	42
AAS466401001	34	AAS467500606	35	AAS468200803	36	AAS472002408	42
AAS466401201	34	AAS467500806	35	AAS468201003	36	AAS472102408	42
AAS466402201	34	AAS467501006	35	AAS468201203	36	AAS472200008	42
AAS466600165	38	AAS467501206	35	AAS468400365	37	AAS472300008	42
AAS466600245	38	AAS467600243	33	AAS468400406	37	AAS472400008	42
AAS466600365	38	AAS467600363	33	AAS468400506	37	AAS472600365	37
AAS466600406	38	AAS467600403	33	AAS468400606	37	AAS472600606	37
AAS466600506	38	AAS467600603	33	AAS468400806	37	AAS472600806	37
AAS466600606	38	AAS467600803	33	AAS468401006	37	AAS472601006	37
AAS466600806	38	AAS467601003	33	AAS468401206	37	AAS472601206	37
AAS466601006	38	AAS467601203	33	AAS468601206	40	AAS472700365	35
AAS466601206	38	AAS467700243	33	AAS468601506	40	AAS472700606	35
AAS466601506	38	AAS467700363	33	AAS468602206	40	AAS472700806	35
AAS466800163	38	AAS467700403	33	AAS469500363	32	AAS472701006	35
AAS466800243	38	AAS467700603	33	AAS469500503	32	AAS472701206	35



Index - Article Numbers

Article No.	Page	Article No.	Page	Article No.	Page	Article No.	Page
AAS472800365	32	AF4411311300	14	AS3647624810	63	ASO903670	19
AAS472800505	32	AF4411311400	14	AS3647625250	63	ASO903680	20
AAS473200806	43	AF4411311500	14	AS3647773230	63	ASO991011	21
AAS473300806	43	AF4411311600	14	AS44008003	31	ASO991110	20
AAS473301006	43	AF4411311700	14	AS44008009	31	ASO992011	24
AAS473301206	43	AF4411311800	14	AS44008010	31	ASO994011	27
AAS67012060	41	AF4411311900	14	AS44008014	31	ASO995022	20
AAS67012080	41	AF4411312000	14	AS44008015	31	AT31001000	69
AAS67012100	41	AF4411312100	14	ASC25430	29	AT31002200	69
AAS67012120	41	AF4411312200	14	ASC025435	29	AT31002300	69
AAS68011000	39	AF4411312300	14	ASC3611478	28	AT31002500	70
AAS68012000	39	AF4411312500	14	ASC718070	30	AT31002600	69
AAS68013000	39	AM400201100	63	ASC718906	40	AT31002800	70
AAS68014000	39	AM43021000	31	ASC742069	29	AT31003000	70
AAS854303208	40	AM44008000	31	ASC742077	29	AT31004000	70
AAS867100603	41	AM45001000	30	ASC742080	29	AT31005000	69
AAS867100803	41	AMC020000	30	ASC74765	29	AT31006000	70
AAS867101003	41	AMC718010	30	ASC780920B	29	AT31006100	70
AAS867101203	41	AMC739000B	28	ASF100100	27	AT31014001	70
AAS867101503	41	AMF100000	27	ASF100200	27	AT31101000	71
AAS867101803	41	AMK170000	19	ASF100300	27	AT31120897	69
AAS867102203	41	AMK170002	19	ASK2999940045	22	AT31302001	72
AAS867300018	39	AMK172000	19	ASK2999940046	22	AT31304250	15
AAS867300028	39	AMK173000	19	ASK3199940008	24	AT31344402	75
AAS867300038	39	AMK175000	20	ASK3199940901	27	AT31360350	72
AAS867300048	39	AMK175010	20	ASK3199940991	26	AT31400280	15
AAS867300058	39	AMK180000	21	ASK3199941010	26	AT31400380	15
AAS867300068	39	AMK180011	21	ASK3199941020	26	AT31401002	71
AAS872000803	41	AMK185000	21	ASK3199941030	26	AT31401180	15
AAS872001003	41	AMK185010	21	ASK6099940045	22	AT31402180	15
AAS872001203	41	AMK270000	24	ASK6099940046	22	AT31402250	15
AAS872100406	42	AMK270010	24	ASK66000030150	23	AT31403180	15
AAS872100606	42	AMK280100	23	ASK6999940006	19	AT31404180	15
AAS872100806	42	AMK280010	23	ASO312082	26	AT31405000	71
AAS903700808	41	AMK281010	23	ASO312501	25	AT31405180	15
AAS903701008	41	AMK281100	23	ASO312520	25	AT31406180	15
AAS903701208	41	AMK282010	23	ASO312530	25	AT31408000	75
AAS903701508	41	AMK282100	23	ASO312540	25	AT31409000	79
AF3100013	56	AMO110000.3	20	ASO312570	28	AT31409001	79
AF3100025	56	AMO110001.3	20	ASO312581	28	AT31409180	15
AF3102010	56	AMO230009.3	22	ASO312582	28	AT31410180	15
AF3600013	56	AMO230018.3	22	ASO319000	25	AT31413180	15
AF3600025	56	AMO310001	24	ASO319934	25	AT31413250	15
AF3602010	56	AMO310002	24	ASO319936	25	AT31444000	75
AF390013001	56	AMO310007	24	ASO319940	28	AT31444001	75
AF390015001	56	AMO530005	17	ASO539001	17	AT31451000	69
AF390024001	56	AMO540000	18	ASO539910	17	AT31451001	70
AF4411311000	14	AS3647622500	63	ASO539920	17	AT32033000	75
AF4411311100	14	AS3647622520	63	ASO540001	18	AT32038000	75
AF4411311200	14	AS3647624580	63	ASO540001	18	AT32040000	15

Index - Article Numbers

Article No.	Page	Article No.	Page	Article No.	Page	Article No.	Page
AT32042000	15	AT929504	72	BR84805400M1BO	11	GT551115001	58
AT32046051	13	AT953203	71	BR84805600M1BO	11	GT551124001	58
AT32046052	13	AT953214	71	BR84806800M1BO	11	GT551215001	58
AT32046053	13	AT954224	71	BR848T2800M1BO	12	GT551315001	58
AT32046054	13	AT954225	71	BR848T5600M1BO	12	GT551515001	58
AT32046055	13	AT956903	72	BR848T5700M1BO	12	GT560113001	55
AT32046056	13	AT956904	72	BR848T5800M1BO	12	GT560115001	55
AT32046057	13	AT959201	72	BR848T6800M1BO	12	GT560120001	55
AT32046058	13	AX0003543	79	BR85002800M1BO	12	GT561113001	55
AT32046059	13	AX0003544	79	BR85005000M1BO	12	GT561115001	55
AT32046060	13	AX34001000	76	BR85006800M1BO	12	GT562113001	55
AT32051080	75	AX34002000	76	BR850T2800GBBO	12	GT562115001	55
AT32052500	75	AX34003000	76	BR850T5600M1BO	12	GT563113001	55
AT32053001	74	AX34004000	76	BR850T5700M1BO	12	GT563115001	55
AT32053002	74	AX34006000	76	BR850T5800M1BO	12	GT564113001	55
AT32053003	74	AX34009000	76	BR850T6800M1BO	12	GT564115001	55
AT32053004	74	AX34040000	3	BR88000300M1BO	13	GT565113001	55
AT32053005	74	AX34200000	52	BRTIT02800M1BO	13	GT565115001	55
AT32053006	74	AX36225002	8	BS10002000DEBO	4	GT570014001	56
AT32053007	74	AX36225003	8	EB400620001	61	GT571114001	56
AT32053008	74	AX36225005	8	EC800013001	60	GT572114001	56
AT32053009	74	AX36310003	9	EC800020001	60	GT573114001	56
AT32053010	74	AX36340004	9	EC801613001	60	GT574114001	56
AT32053011	74	AX36500000	15	EC801620001	60	GT575114001	56
AT32053012	74	BD50002000GBBO	5	EC802613001	60	GX504007	57
AT32053013	74	BD50102000GBBO	5	EC802620001	60	GX504107	57
AT32053014	74	BD51002000DEBO	5	EC803613001	60	GX504207	57
AT32053016	74	BD70001100GBBO	9	EC803620001	60	GX504307	57
AT32053017	74	BD70504700M1BO	9	EC804613001	60	GX504407	57
AT32053019	74	BD72002800M1BO	10	EC804620001	60	P901201	73
AT32053020	74	BD75002200DEBO	10	EC811713001	60	WB074002002	46
AT32053021	74	BD75002700DEBO	10	EC811720001	60	WB200013003	45
AT32053022	74	BH500031	8	EC812713001	60	WB200020012	45
AT32053100	74	BH500032	8	EC812720001	60	WB250020001	45
AT32055000	75	BH500033	3	EC813713001	60	WB250024001	52
AT32086000	72	BH600031DE	7	EC813720001	60	WB250613001	45
AT322100	76	BH605031M1	7	EC814713001	60	WB250620001	45
AT33011100	78	BH610031	7	EC814720001	60	WB251620001	45
AT33012100	78	BH660031DE	7	EH390002001	61	WB251613001	45
AT33013100	78	BH670031DE	8	ES205045001	60	WB255020001	46
AT33051000	72	BR20005900M1BO	10	ES205045001	60	WC410155001	53
AT37001020	76	BR40501400DEBO	3	EM702020001	61	WC420155001	53
AT37001100	76	BR41002000GBBO	4	EM703020001	61	WC420255001	53
AT37001200	76	BR44006600DEBO	3	ES200013501	61	WC430155001	53
AT37004000	77	BR54002200M1BO	4	ES200013502	61	WC430255001	53
AT37008000	77	BR59005000M1BO	4	ES200013503	61	WC440155001	53
AT37010000	77	BR77702700M1BO	11	GT525113001	66	WC470155001	53
AT37012000	77	BR77705000M1BO	11	GT525120001	66	WC470120001	46
AT929502	72	BR77802400M1BO	11	GT525213001	66	WC472220001	46
AT929503	72	BR84802800M1BO	11	GT525313001	66	WC474220001	46



ЦИКЛЕВОЧНАЯ
КОМПАНИЯ
WWW.1PARKET.RU +7 (495) 545-25-85



Index - Article Numbers

Article No.	Page	Article No.	Page	Article No.	Page	Article No.	Page
WC490120001	46	WT300613012	48				
WC490155001	53	WT300620001	48				
WF21001302	58	WT300913012	48				
WF21002002	58	WT300920001	48				
WF220020001	58	WX100006001	50				
WH330045001	47	WX700020001	57				
WH341045001	47	WX900020001	57				
WM640020007	53						
WM650013023	65						
WM650020006	53						
WM650020010	63						
WM700013005	66						
WM700020001	66						
WM710013489	79						
WM760013001	65						
WM760020001	65						
WP500313001	64						
WP500320001	64						
WP511013001	64						
WP511020001	64						
WP595013016	64						
WP595020002	64						
WP615013001	66						
WT133013002	49						
WT133020002	49						
WT133313002	49						
WT133320002	49						
WT133613001	49						
WT133620001	49						
WT133920001	49						
WT135024001	52						
WT136624001	52						
WT153346001	47						
WT153646001	47						
WT153946001	47						
WT155346001	47						
WT155646001	47						
WT155946001	47						
WT180646001	49						
WT190646001	48						
WT230013001	49						
WT230020001	50						
WT230313001	50						
WT230320001	50						
WT230324001	50						
WT230613001	50						
WT230620001	50						
WT230624001	50						
WT300313012	48						
WT300320001	48						



The Full System for All Your Wood Flooring Needs

You are now holding the most comprehensive guide on our full range of sustainable innovations. Here, you will find detailed product information and application advice for the installation, renovation and maintenance of wooden floors.

All Bona products are optimised for complete compatibility and are specially developed to meet the highest functional, aesthetic and environmental requirements. In this edition, you will find exciting new solutions that take our passion for wood floors one step further. Open up and discover everything you need to bring out the best in wooden floors.