

# Bona Concrete Disc by KUNZLE & TASIN

The Bona Concrete Disc is designed to allow contractors with a Bona FlexiSand to prepare concrete surfaces. Comprising of a drive plate together with the choice of 3 cutting segments the Bona Concrete Disc allows substrates to be cleaned and prepared for the installation of flooring.

## Technical data

- Compatible with Bona FlexiSand
- Dimensions 405 mm diameter
- No. of cutting segments 4; 110 mm triangular shape
- Weight 5.3 Kg

## Directions for use


The Concrete Disc is attached exactly as other plates to the FlexiSand. When using a Bona FlexiSand 1.9 greater efficiency can be gained by using the Concrete Disc with the optional FlexiSand weights.

N.B. Additional weights cannot not be used with a FlexiSand 1.5

The cutting segments are magnetic which allows them to be easily changed with no need to remove screws, etc.

There are 3 cutting segment types to choose from:

- **Diamond:** designed to be used primarily to prepare concrete, level concrete surfaces and to remove hard deposits from the sub-floor
- **PCD Split:** designed to remove thin layers of adhesive, paint and other coatings
- **PCD Maxi:** designed to remove thick layers of adhesive, epoxy coatings and softer deposits from the subfloor. The PCD Maxi Segment should be installed with the cutting edge in the same direction as the machine's rotation – see image below.



Cutting direction

The condition of the segments should be monitored closely and checked after 30 minutes of use. If the segments look worn or damaged an incorrect segment selection for the job may have been made.



**1** ЦИКЛЕВОЧНАЯ  
КОМПАНИЯ  
WWW.1PARKET.RU +7 (495) 546-26-86

**Bona**<sup>®</sup>

Phone 1300 882 806

The Bona Concrete disc may be used in conjunction with the Bona DCS equipment. It is **very important** that the filters are cleaned regularly during use. When preparation has been completed remove the DCS Coarse filter and carefully cleaned to ensure that no concrete dust residues remain.

## Segment Selector

<u>Subfloor</u>	<u>Diamond</u>	<u>PCD Split</u>	<u>PCD Maxi</u>
Soft concrete	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Hard concrete	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Screed	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Anhydrite screed	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Tile mortar residues	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Adhesive – thin < 1 mm	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Adhesive – thick > 1 mm	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Silane adhesive	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Epoxy coating	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Polyurethane coating	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Paint	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Carpet foam	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Other carpet underlays	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Key:  Best Choice     Useable     Not useable

**NB.** Please note that the Bona Concrete disc is not designed to be used to burnish / polish a concrete floor or as a specialist concrete grinding option. It is designed for contractors to have the option to prepare surfaces ready for the installation of timber flooring without the need for specialist equipment.

## Important notes

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. The User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. Bona can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt make a preliminary test. The User is required to read and understand all information contained on package labels and safety data sheets before using this product.