

# TECHNICAL INFORMATION

## DeckPrepare



ЦИКЛЕВОЧНАЯ  
КОМПАНИЯ  
WWW.1PARKET.RU +7 (495) 545-25-85



NEW

### "Anti-Aging" for your wood deck: effective support for the protective final treatment

Primer for wooden decks in outdoor areas. Simple application, double effect: LOBADUR DeckPrepare effectively strengthens protection and adhesion of the subsequent surface finishing with LOBASOL DeckOil / Color or LOBADUR DeckFinish Color. Through powerful stabilization of the wood's own ingredients, LOBADUR DeckPrepare delays the natural graying of the wood.

- Delays the weather-related graying of wood
- Strengthens the protective effect of the subsequent surface refinement
- Improves the adhesion of the subsequent coating to the substrate
- Simple and safe application
- Color- and odorless
- Quick-drying
- Environmentally friendly
- Required in a system with LOBADUR DeckFinish Color. Optional application before impregnation with LOBASOL DeckOil / Color

#### Recommended use:

Suitable for wooden decks, patios, outdoor furniture and other objects made from wood that are used outdoors.

## Technical Data

#### Art.-no.

11841

#### Item-#:

LO-FI-303



1 Gal.



4



200

#### Solids

16.4 ±2%

#### Viscosity DIN 4

11 ±2s

#### Storage and transportation

Shelf life: 12 months in unopened containers. Store and transport between 40°F to 75°F (5°C to 25°C). KEEP FROM FREEZING.

#### US Regulatory VOC

< 2 g/l

31/03/2021



# TECHNICAL INFORMATION

## DeckPrepare



ЦИКЛЕВОЧНАЯ  
КОМПАНИЯ  
WWW.1PARKET.RU +7 (495) 545-25-85



### Information for Use

- For professional Use only!
- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our LOBA-WAKOL Technical Service at 1-800.230.6456.
- Do not thin. Do not add water.
- Transfer material to a LOBATool coating bucket before applying.
- Optimum processing conditions at +60°F to +80°F (15°C to 25°C), relative humidity 40% to 75%, material temperature +60°F to +80°F (15°C to 25°C).
- Do not apply to surfaces exposed to hot or strong sunlight, as the applied coating may dry too quickly. Do not apply if rain is expected within 3 hours of application.
- If in doubt, create a test area to determine compatibility, adhesion and appearance. The results may vary depending on the type of wood, especially with oily, resinous and chemically pre-treated woods.
- Avoid drops falling on the surface, smooth out any drops directly with a brush.
- **WARNING!** If you scrape, sand or remove old paint from wood floors, you may release lead dust. Follow local and/or federal requirements for lead removal. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### Application Tool

LOBATool oil brush, soft brush.

### Coverage

350-400 square feet per 1 gal container. Actual material coverage may vary depending on the type of wood, wood moisture and the weathering condition of the surface. With strongly weathered surfaces, a significantly lower coverage should be expected.

### Drying time

- Drying 1 hour. Wait for complete drying

### Preparation:

Please refer to the LOBACARE DeckDegrayer technical information for optimal surface pretreatment.

### Application:

- Surface must be completely dry before application
- Apply one layer of LOBADUR DeckPrepare.
- Drying 1 hour. Wait for complete drying
- Then apply LOBASOL DeckOil / Color or LOBADUR DeckFinish Color according to the Technical Information.
- To maintain the visual value of the decking, we recommend an annual basic cleaning and recoating of the decking.

### Compatibility

When this product is used in combination with other LOBA products the Technical Information of these products must be followed. Always prepare test areas to determine suitability of other products than LOBA.

31/03/2021



# TECHNICAL INFORMATION

## DeckPrepare



ЦИКЛЕВОЧНАЯ  
КОМПАНИЯ  
WWW.1PARKET.RU +7 (495) 545-25-85



### General guidelines

**Cleaning of tools:** Clean tools with solvents such as brush cleaner.

**Cure Time:** The stated drying and cure times are based on ideal conditions (68°F, 50% rH) at the recommended application rates. Recommended conditions are 50°F-80°F/40%-65%rH. Insufficient ventilation, high humidity, lower temperatures can prolong the curing process considerably. Do not use safety covers on floor, do not replace carpets or rugs and also do not clean floors with a damp cloth before the final curing has been reached. Remaining excessive material will prolong curing. On some exotic woods curing time can be extended.

**Use of LOBADUR DeckFinish Color without LOBADUR DeckPrepare:** While it is possible to use LOBADUR DeckFinish Color without LOBADUR DeckPrepare, the use of LOBADUR DeckPrepare significantly improves the adhesion properties of the finish to the substrate and increases the application safety.

**Safety Precautions:** Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink or smoke in working areas. Wear suitable safety gloves. Clean left-overs off of hands. Change soiled clothes.

**First Aid:** If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally this product does not cause skin irritation. Call a physician if irritation occurs.

**Special Information** The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol.

The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website [www.loba-wakol.com](http://www.loba-wakol.com). You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

31/03/2021

